



Alfa Laval AC30EQ / ACH30EQ

Brazed plate heat exchanger for air conditioning and refrigeration

Alfa Laval AC brazed plate heat exchangers provide efficient heat transfer with a small footprint. They are specifically designed to work in air conditioning and refrigeration applications as evaporators and condensers in chillers and heat pumps.

Applications

- Evaporator
- Condenser
- Cascade systems

Benefits

- Compact
- Easy to install
- Self-cleaning
- Low level of service and maintenance is required
- All units are pressure and leak tested
- Gasket free

Design

The brazing material seals and holds the plates together at the contact points ensuring optimal heat transfer efficiency and pressure resistance. Using advanced design technologies and extensive verification guarantees the highest performance and longest possible service life.

Different pressure ratings are available for different needs.

The integrated distribution system ensures an even distribution of the refrigerant throughout the plate package.

Based on standard components and a modular concept, each unit is custom-built to meet the specific requirements of each individual installation.

Suitable with most HFC, HFO and natural refrigerants.

Examples of connections



External thread





Internal thread



Technical Data

Standard materials

| Cover plates | Stainless steel | |
|----------------|-----------------|--|
| Connections | Stainless steel | |
| Plates | Stainless steel | |
| Brazing filler | Copper | |

Dimensions and weight¹

| 9 + (1.52 * n) |
|-------------------|
| 0.35 + (0.06 * n) |
| 1 + (0.09 * n) |
| 2.2 + (0.2 * n) |
| |

- n = number of plates 1.
- 2. Excluding connections


Standard data

| Volume per channel, litres (gal) | 0.028 (0.0072) | |
|--|----------------|--|
| Max. particle size, mm (inch) | 0.6 (0.024) | |
| Max. flowrate ¹ m ³ /h (gpm) | 8.8 (39) | |
| Flow direction | Parallel | |
| Min. number of plates | 4 | |
| Max. number of plates | 120 | |
| | | |

Water at 5 m/s (16.4 ft/s) (connection velocity) 1.

Dimensional drawing

Measurements in mm (inches)





(12.79) 269 (10.59)


325 (

Design pressure and temperature

AC30EQ/ACH30EQ - PED approval pressure/temperature graph







Designed for full vacuum.

Alfa Laval plate heat exchangers are available with a wide range of pressure vessel approvals. Please contact your Alfa Laval representative for more information.

NOTE: Values above are to be used as an indication. For exact values, please use the drawing generated by the Alfa Laval configurator or contact your local Alfa Laval representative.

CHE00003EN 2016-04

Alfa Laval reserves the right to change specifications without prior notification.

Alfa Laval is a trademark registered and owned by Alfa Laval Corporate AB.

How to contact Alfa Laval

Contact details for all countries are continually updated on our website. Please visit www.alfalaval.com to access the information direct.



info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289