

housings 2P SX

for cartridges with standard flat seals



Cadet

Junior

Senior

APPLICATIONS

Filtration and treatment of water with neutral pH and drinking water.

Domestic use: filtration of drinking water, protection of taps, boilers, washing machines, and other installations.

Technical use: pre-filtration, micro-filtration; protection of pumps, heating systems, softeners, demineralising and chlorine-removing appliances, reverse osmosis units.

WORKING CONDITIONS

Max working pressure _____ 7 BAR

Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

Head: ABS


Transparent bowl: SAN.

O-ring: ETP

Breather-valve: body polypropylene, O-ring ETP.

IN/OUT threads: CW 614 N brass inserts.

Cartridge height	housings with transparent bowl AS IN/OUT female threads with FO brass inserts	IN/OUT threads	mm	
			A	B
4"	Cadet 2P AFO SX AS	3/4"	169	133
4"	Cadet 2P BFO SX AS	1"	175	145
7"	Junior 2P AFO SX AS	3/4"	241	133
7"	Junior 2P BFO SX AS	1"	247	145
10"	Senior 2P AFO SX AS	3/4"	315	133
10"	Senior 2P BFO SX AS	1"	321	145



VARIANTS available on minimum quantity

FP female plastic IN/OUT threads, BSP type 3/4" e 1".

AB housings with opaque bowl, impermeable to the light.



accessories



-V- Spanner



wall bracket



wall bracket screws



3/4" and 1" brass nipples with O-ring



4", 7", 10" diffuser tubes