

# housings Duplex Plus 3P AX

for quick-fit cartridges with double O-ring



Medium Junior Master Senior

### APPLICATIONS

Filtration and treatment of water with neutral pH and drinking water. The exclusive DUPLEX housings allow faster and safer installations of serial filtration units.

**Domestic use:** filtration and treatment of drinking water, protection of taps, boilers, washing machines, and other installations.

**Technical use:** pre-filtration, micro-filtration; protection of pumps, heating systems, softeners, demineralising and chlorine-removing appliances, reverse osmosis units.

### WORKING CONDITIONS

Max working pressure \_\_\_\_\_ 8 BAR  
Max working temperature \_\_\_\_\_ 45°C

### SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

**Head and ring nut:** reinforced polypropylene.


**Transparent bowl:** SAN.

**O-ring:** ETP.

**Breather-valve:** body polypropylene, O-ring ETP.

**IN/OUT threads:** CW 614 N brass inserts.

Cartridge height	housings with transparent bowl AS IN/OUT female threads with FO brass inserts	IN/OUT threads	mm	
			A	B
5"	Medium Duplex Plus 3P AFO AX AS	3/4"	191	275
5"	Medium Duplex Plus 3P BFO AX AS	1"	191	275
7"	Junior Duplex Plus 3P AFO AX AS	3/4"	241	275
7"	Junior Duplex Plus 3P BFO AX AS	1"	241	275
10"	Senior Duplex Plus 3P AFO AX AS	3/4"	315	275
10"	Senior Duplex Plus 3P BFO AX AS	1"	315	275
20"	Master Duplex Plus 3P AFO AX AS	3/4"	571	275
20"	Master Duplex Plus 3P BFO AX AS	1"	571	275



### VARIANTS available on minimum quantity

**FP** female plastic IN/OUT threads, BSP type 3/4".

**AB** housings with opaque bowl, impermeable to the light.



-U- spanner



-D- wall bracket



wall bracket screws



3/4" and 1", brass nipples with O-ring