

Betapure™ AU

Cartridges & Capsules

Rigid Filter Media

- ☑ Precise Contaminant Removal
- ☑ Improved Effluent Quality
- ☑ Reduced Operating Costs

Applications

Coating

- Magnetic Media
- High Quality Paint
- Film Coatings
- Resins
- Ink

Electronics

- Pre RO
- Water Slurries
- Ceramic Slurries
- Chemical Mechanical Polishing
- Cathode Ray Tube Production
- Disc Cleaning

General Industrial

- Desalination
- Plating
- Machine Tool Coolant
- Process Water

Chemical/Petrochemical

- Process Water
- Pre RO
- Amine
- Fine Chemicals
- MTBE

Food & Beverage

- Bottled Water
- Pre RO
- Blend Water
- Wash Water

Pharmaceutical

- Water
- Solvents and Chemicals
- Pre RO

Betapure AU Designed for Optimum Filtration Quality

Betapure AU Series filter cartridges and capsules set the standard for filtration performance. Offering more grades with absolute removal ratings than competitive filters, the controlled pore size of the Betapure AU filter matrix allow for absolute distinction between cartridge grades to provide the most accurate and consistent filtration.

The Betapure AU Series filter provides:

- Precise Contaminant Removal
- Consistent Effluent Quality
- Superior On-stream Service Life

Betapure AU filters, available in 18 distinct grades with absolute ratings from 2 to 190 microns to tailor the exact selection of performance characteristics for the greatest filtration economy by providing distinct removal cut-off points by particle size. Betapure AU filter manufacturing combines advanced incoming material quality assurance, exacting in-process controls and extensive final product testing and verification. The result is a filter product that provides consistent filtration lot-to-lot, filter-to-filter.

Features and Benefits

Absolute ratings

- Consistent and reproducible contaminant removal.
- To meet demanding filtration quality standards in today's market, absolute ratings will provide product consistency and product yields.

Rigid structure

- Eliminates cartridge by-pass and unloading to provide consistent filtration from start to finish.
- The rigid filter structure retains consistent pore size even under severe process conditions. Changes such as those caused by pump fluctuations, stopping and restarting the system, or high differential pressure will have minimal, if any effect on product consistency.

Depth filtration

- Excellent removal of deformable contaminants for consistent effluent.
- Depth filtration removes deformable contaminants to reduce or totally eliminate rework or product quality rejection.

Gasket design

- Eliminates by-pass from poor or damaged seals.
- Critical to any filtration process is the elimination of filter by-pass. A closed cell polyethylene foam gasket ensures proper cartridge sealing when using knife-edge housing system.

Lower pressure drop

- Provides long service life while using smaller filter housings.
- Minimising flow restriction dramatically reduces filtration cost. Lower pressure drops mean increased filter life, product throughput and permit the use of fewer filters to achieve a given flow vs. differential pressure.

Available in standard cartridge and disposable capsules

- Wide range of filter sizes allows more appropriate filter sizing for batch and continuous processes.
- Filters appropriately sized for a specific application reduces total filtration costs including purchase, installation and disposal.

For more information contact:

info@lenntech.com

www.lenntech.com

Tel. +31-15-261.09.00

Fax. +31-15-261.62.89

Performance Construction for Precision Filtration

The Rigid Construction Advantage

Betapure AU filter manufacturing utilises state-of-the-art technology to produce a clear, rigid, filter structure with consistent and reproducible filtration characteristics. The filter matrix is constructed using long bi-component fibres, each fibre having an inner core and an outer sheath (see picture at the right). Betapure AU filters are available in two bi-component fibre structures, polypropylene/polyethylene or polyester/co-polyester, to provide the greatest range of process compatibility.

The bi-component fibres of the filter matrix are thermally bonded by utilising the difference in melt temperatures of the two fibre components. Heating the matrix to the melt temperature of the polyethylene sheath, but below that of the polypropylene core, causes the fibre-to-fibre bond at every contact point. The high degree of fibre-to-fibre bonding provides a rigid structure that eliminates the need for a core support and any possibility of media migration.

The Betapure AU Series filter ensures that the unwanted particles are removed because:

- The rigid structure maintains its porosity throughout the filter life.
- The depth structure removes more difficult deformable contaminants.


With 18 distinct grades with absolute ratings from 2 to 190 microns to permit the exact filter performance selection, Betapure AU filters provide the greatest filtration economy available.

Enhanced Effluent Consistency

The sole purpose of filtration is to remove contaminants or materials that compromise product quality - throughout the entire service life of the filter. A non-rigid filter's pore structure changes as the system differential pressure increases. The result is changing filtration efficiency and inconsistent performance during the filter service life. This can only be corrected by a filter that retains its pore structure. Betapure AU Series filters are manufactured with precise control of the filter porosity coupled with the rigid Betapure AU structure to maintain its porosity throughout its service life. The result is consistent filtrate quality that is reproducible time after time, week after week, year after year.

Removal Ratings

3M Purification uses a Multiple Parameter Characterisation (MPC) that, unlike single point evaluations, determines a removal rating over a range of particle sizes (multi-value) and the filter's service life (multi-point). The parameters measured include particle counts, turbidimetric efficiencies and removal efficiencies.



Grade	Rating (µm)		Grade	Rating (µm)	
	Absolute	Nominal		Absolute	Nominal
Z13 - 020	2	0.2	B11	20	5
Z13 - 030	3	0.3	C11	30	10
Z13 - 050	5	0.5	E11	40	20
Z11 - 060	6	0.6	G11	70	30
Z11 - 070	7	0.7	L11	90	50
Z11 - 080	8	0.8	Q11	100	75
Z11 - 100	10	0.9	V11	140	100
Z11 - 120	12	1	W11	160	150
Z11 - 150	15	3	X11	190	175

Grade	Rating (µm)	
	Absolute	Nominal
A12	8	3
B12	20	5
C12	30	10
E12	40	20
G12	70	30



Filtration Advantage - Rigid Construction

Comparing Filtration Characteristics

The unique structure of the Betapure AU Series cartridge provides filtration characteristics that are more consistent than competitive filter cartridges. The following curves show the filtration characteristics of the Betapure AU Series cartridge compared to other polyolefin cartridges and typical polypropylene melt-blown and string-wound cartridges of equivalent removal rating.

Scientific Applications Support Services (SASS)


The cornerstone of 3M Purification's philosophy is service to customers, not only in product quality and prompt delivery, but also in validation, application support and the sharing of scientific information.

3M Purification's Scientific Applications Support Services (SASS) works closely with customers to solve difficult filtration challenges and to recommend the most efficient, economical filter systems. SASS specialists can perform on-site testing and utilise filtration applications expertise to partner with customers. 3M Purification resolves filtration problems promptly and efficiently in a cost-effective, confidential manner with a commercial support group consisting of 3M Purification's in-house customer service staff, application specialists, and engineering services. 3M Purification's broad distributor base and sales offices provide worldwide customer service, local inventory and field support in virtually every major centre of manufacturing.


Betapure AU Series Filter

Note that the Betapure AU filter exhibits excellent filtration capability during its service life. This is evident by the close proximity of the curves to one another. From start to finish, the filter performance does not vary. The rigid Betapure AU filter structure resists deformation, particle unloading or filter by-pass and provides consistently high particle removal efficiency.

Betapure AU Series Filter



Other Polyolefin Bi-component Filters



Other Polyolefin Bi-component Filters

Other bi-component filters may look like Betapure AU Series cartridges, but they can't match the performance. Note that immediately after the filter is put into service, the efficiency drops but then recovers to the initial efficiency. The inconsistent efficiency exhibited during the service life is reflected in poor effluent and is not reliable enough to satisfy the demand for exceptional product quality.

How these tests were conducted...

3M Purification uses a Multiple Parameter Characterisation (MPC) that, unlike single point evaluations, determines a removal rating over a range of particle sizes (multi-value) and the filter's service life (multi-point). The parameters measured include particle counts, turbidimetric efficiencies and removal efficiencies.

Conditions of Test:	
Flow:	11.4 litres/min
Fluid:	water

Filtration Advantage - Rigid Construction


Flow Characteristics

Betapure AU Series exhibits superior flow characteristics for the same removal rating as other polyolefin fibre based cartridges.

The curve shows that at a given flow rate the pressure drop across Betapure AU Series is considerably lower than competitive products.

The benefits of lower pressure drops are:

- Longer cartridge life
- Higher throughputs
- Smaller housing requirements
- Lower overall costs



Chemical Compatibility


Betapure AU Series filters are composed of bi-component fibres, either polypropylene/polyethylene or polyester, both offering broad chemical compatibility. Note that compatibility is always a function of exposure time, operating temperature and chemical concentration. If compatibility is in question, 3M Purification recommends that the filter be tested. For more general information about Betapure AU Series filter chemical compatibility, contact your local distributor.

Regulatory Compliance

Standard Betapure AU Series filters (polypropylene / polyethylene) comply with FDA regulation CFR 21. Betapure AU filters have also been USP XXI Class VI (Safety Test for Plastics) tested and have been deemed suitable for pharmaceutical application. Detailed information about application compatibility and samples for testing are available by contacting your local 3M Purification representative.

String-Wound Filter

The competitive cartridge exhibits erratic filtration characteristics that dramatically fluctuate in response to increasing differential pressures.



Melt-Blown Filter

The compressible structure of a melt-blown filter exhibits wide fluctuations in performance efficiency as the system pressure changes. Such filtration characteristics lead to inconsistent and unpredictable product quality.




Table 4: Betapure AU filter flow information

Grade	Absolute Rating (µm)	Specific Pressure Drop per 10" Cartridge (mbar / litre per min)
Polyolefin Betapure AU (11 Series)		
B11	20	5.10
C11	30	2.18
E11	40	0.89
G11	70	0.55
L11	90	0.36
Q11	100	0.18
V11	140	0.127
W11	160	0.091
X11	190	0.074
Polyester Betapure AU (12 Series)		
A12	8	2.55
B12	20	2.00
C12	30	1.44
E12	40	0.55
G12	70	0.36
Polyolefin Betapure AU (Z13 Series)		
Z13-020	2	16.00
Z13-030	3	8.6
Z13-050	5	5.3
Polyolefin Betapure AU (Z11 Series)		
Z11-060	6	5.6
Z11-070	7	5.3
Z11-080	8	5.1
Z11-100	10	1.9
Z11-120	12	1.0
Z11-150	15	3.5

* For multiple cartridge lengths, divide total flow by the number of single length equivalents.

Operating Data

Operating Parameter	Description
Polyolefin Betapure AU	
Max. operating temperature	80 °C
Max. differential pressure*	5.5 bar at 20 °C
Polyester Betapure AU	
Max. operating temperature*	120 °C
Max. differential pressure*	5.5 bar at 20 °C

* Betapure AU's rigid structure will tolerate up to 5.5 bar. Normally 3M Purification recommends the use of the lowest possible flow rate and filter re-placement at 2.4 bar to enhance both filter life and filtration efficiency.

Disposal

Betapure AU Series filter cartridges can be incinerated, shredded or crushed after to reduce the overall disposal costs. For more information about Betapure AU disposal, ask your local 3M Purification distributor.

Cartridge Configurations

All Betapure AU Series cartridges are available in continuous multiple lengths up to 60" (1524 mm) long, with various end treatments to fit your current housing (see ordering guide).

Table 3: Betapure AU Series Cartridge Parameters

Parameter	Description
Length * (nominal)	9" ¾ to 60" (248 mm to 1524 mm)
Inside Diameter (nominal)	25.4 mm
Outside Diameter (nominal)	63.5 mm

* Other sizes available on request, consult factory

Special Configurations

Betapure AU is available in special configurations upon request. The length, inside and outside diameters can be modified for your specific needs. Consult your local 3M Purification distributors for more information.

How to determine Cartridge Flow Rates/Pressure Drop Sizing

Betapure AU exhibits superior flow characteristics for the same micron rating compared to other fibre based cartridges. This allows for longer cartridge life, higher throughput and smaller housing requirements. Table 4 provides flow information for Betapure AU filters in aqueous fluids.

The specific pressure drop values (mbar/ litre per min) per 10" cartridge at 1 centipoise are provided for each filter grade. For fluids other than water, multiply the specific pressure drop value by the viscosity in centipoises. The specific pressure drop values may be effectively used when three of the four variables (viscosity, flow, differential pressure and cartridge grade) are set.

Example 1:

Determine the initial pressure drop for water flowing at 30 litre/min per 30" (C11) 30 µm cartridge.
 Fluid = Water (1 centipoise)
 Flow = 30 litre/min
 Flow per 10" cartridge = 30 : 3 = 10 litre/min
 Specific pressure drop from column 3 of Table 4 = 2.18 mbar / litre per min
 Calculate: 2.18 x 10 = 21.8 mbar

Example 2:

Determine the oil flow rate at an initial pressure drop of 140 mbar per 10" (E11) 40 µm cartridge.
 Fluid = 100 centipoises oil
 Initial differential pressure = 140 mbar
 Specific pressure drop from column 3 of Table 4 = 0.89 mbar / litre per min
 Multiply psi/gpm x viscosity in centipoises = 0.89 x 100 = 89
 Calculate: 140 mbar/89 (mbar/litre per min) = 1.57 l/min

Filter Systems


3M Purification manufactures a full line of Betapure AU compatible filter housings and a wide variety of industrial filter media to meet most application requirements. Housing Models are available for both air and liquid applications in a wide range of construction materials, from plastics to PED Cat. IV and ATEX compliant 316L stainless steel, to suit a variety of application needs. For more information about 3M Purification filter housings and other filter media, consult your local 3M Purification distributor.

Betapure AU Series Capsules


The Betapure AU Series capsule is a polypropylene encapsulated filter that eliminates the need for a separate filter vessel. Available in a wide range of configurations (see ordering guide) including sanitary flange and hose barb connections, the 2.5" and 5" capsules are ideal for small batch and filter test applications. The following are typical water flow rates for Betapure AU capsules with 1 1/2" sanitary flange connections. Other end connections will affect maximum flow rates, see table below. Consult factory representative for flow rates using optional end connections or visit www.3MPurification.com.



Flow Rates for 5" Capsules
with 1 1/2" Sanitary Flanges at 20 °C



Flow Rates for 2.5" Capsules
with 1 1/2" Sanitary Flanges at 20 °C



Betapure AU Capsule Max. Recommended Flow by Configuration		
End Connection	Maximum Recommended Flow Rate (litre/min)	Housing Pressure Loss (mbar)
1 1/2" Sanitary Flange	22.7 l/min	69 mbar
3/8" FNPT	22.7 l/min	69 mbar
1/2" Hose barb	11.4 l/min	103 mbar
1/4" MNPT	5.7 l/min	165 mbar

Betapure AU Capsule - Materials of Construction	
All Betapure AU Series Filter Media	Bi-component polypropylene/polyethylene fibres
Z11 Filter Media	Includes a polypropylene insert
Z13 Filter Media	Includes a glass paper insert
Capsule Body	Polypropylene
Vent/drain O-rings	See ordering guide

Betapure AU Series filter capsule ordering guide

Type	Grade * Absolute rating (µm)	Configuration	Nominal length	End connections	Vent O-ring option	Packaging Option
AU = Betapure AU	Z13020 = 2 µm Z13030 = 3 µm Z13050 = 5 µm Z11060 = 6 µm Z11070 = 7 µm Z11080 = 8 µm Z11100 = 10 µm Z11120 = 12 µm Z11150 = 15 µm B11 = 20 µm C11 = 30 µm E11 = 40 µm G11 = 70 µm L11 = 90 µm Q11 = 100 µm V11 = 140 µm W11 = 160 µm X11 = 190 µm	C = Capsule	01 = 2.5" 02 = 5"	A = 1 1/2" sanitary flange B = 1/2" hose barb (14 mm) C = 1/4" MNPT D = 3/8" FNPT E = 1/4" - 5/16" - 3/8" tapered hose barb	A = Silicone (MVQ)** B = Fluorocarbon (FPM)** C = Ethylene Propylene (EPDM)**	01 = 1 capsule 03 = box of 3 capsules 20 = box of 20 capsules

Example: AU Z13050 C 01 A A 03

* Grades Z13020 through Z13050 employ a glass paper insert

- Grades Z11060 through Z11150 employ a polypropylene insert

** ISO Designation

Polyolefin Betapure AU cartridge ordering guide

Cartridge Type	Cartridge Length*	Grade / Micron rating Absolute (Nominal)	Betapure AU Media	End Modification	Flat Gasket or O-ring material
AU = Betapure AU	09 = 9 3/4" 10 = 10" 19 = 19 1/2" 20 = 20" 29 = 29 1/4" 30 = 30" 39 = 39" 40 = 40"	B = 20 µm abs (5 µm) C = 30 µm abs (10 µm) E = 40 µm abs (20 µm) G = 70 µm abs (30 µm) L = 90 µm abs (50 µm) Q = 100 µm abs (75 µm) V = 140 µm abs (100 µm) W = 160 µm abs (150 µm) X = 190 µm abs (175 µm)	11 = Polyolefin	A = Millipore B = Code 7 Bayonet Lock C = Code 8 double O-ring D = DOE with hard cap (Length = 10" nominal) E = DOE with hard cap (Length = 9 3/4" nominal) F = Code 3 Double O-ring flat cap	A = Silicone (MVQ)** B = Fluorocarbon (FPM)** C = Ethylene Prop. (EPDM)** D = Nitrile (NBR)**
				N = No End modification	G = Polyethylene N = None

* other lengths on request

** ISO Designation

Example: AU 29 C11 NG

Polyester Betapure AU cartridge ordering guide

Cartridge Type	Cartridge Length*	Grade / Micron rating Absolute (Nominal)	Betapure AU Media	End Modification	Flat Gasket or O-ring material
AU = Betapure AU	09 = 9 3/4" 10 = 10" 19 = 19 1/2" 20 = 20" 29 = 29 1/4" 30 = 30" 39 = 39" 40 = 40"	A*** = 8 µm abs (3 µm) B = 20 µm abs (5 µm) C = 30 µm abs (10 µm) E = 40 µm abs (20 µm) G = 70 µm abs (30 µm)	12 = Polyester	A = Millipore B = Code 7 Bayonet Lock C = Code 8 double O-ring D = DOE with hard cap (Length = 10" nominal) E = DOE with hard cap (Length = 9 3/4" nominal) F = Code 3 Double O-ring flat cap	A = Silicone (MVQ)** B = Fluorocarbon (FPM)** C = Ethylene Prop. (EPDM)** D = Nitrile (NBR)**
				N = No End modification	G = Polyethylene N = None

* other lengths on request

** ISO Designation

***require D or E end modification

Example: AU 09 B12 NN

Betapure AU Z grade cartridge ordering guide

Cartridge Type	Cartridge Length*	Betapure AU Media	End Modification	Flat Gasket or O-ring material	Absolute Removal rating
AU = Betapure AU	09 = 9 3/4" 10 = 10" 19 = 19 1/2" 20 = 20" 29 = 29 1/4" 30 = 30" 39 = 39" 40 = 40"	Z 13 = Polyolefin/Glass Z 11 = Polyolefin/Polyolefin	B = Code 7 Bayonet Lock C = Code 8 double O-ring D = DOE with hard cap (Length = 10" nominal) E = DOE with hard cap (Length = 9 3/4" nominal) F = Code 3 Double O-ring flat cap	A = Silicone (MVQ)** B = Fluorocarbon (FPM)** C = Ethylene Prop. (EPDM)** D = Nitrile (NBR)**	Z13 material only 020 = 2 µm abs 030 = 3 µm abs 050 = 5 µm abs
			N = No End modification	G = Polyethylene	Z11 material only 060 = 6 µm abs 070 = 7 µm abs 080 = 8 µm abs 100 = 10 µm abs 120 = 12 µm abs 150 = 15 µm abs

* other lengths on request

** ISO Designation

Example: AU 20 Z11 BB 100

Important Notice

3M Purification MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Since a variety of factors can affect the use and performance of a 3M Purification product in a particular application, some of which are uniquely within the user's knowledge and control, user is responsible for determining whether or not the 3M Purification product is fit for a particular purpose and suitable for user's method of application.

Limited Warranty

3M Purification warrants it this product to be free from defects in material and workmanship during normal use for a period of one (1) year from the date of shipment from the factory. If the Product(s) is (are) defective within this warranty period, your exclusive remedy and 3M Purification's sold obligations shall be, at 3M Purification's option, to replace or repair the Product(s) or refund the original purchase price of the Product(s). This warranty does not apply to failures that result from abuse, misuse, alternation or damage not caused by 3M Purification Inc. or failure to properly follow installation and use instructions.

Limitation of Liability: 3M Purification will not be liable for any loss or damage arising from the use of the Product(s), whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you.

This warranty gives you specific legal rights and you may have other rights which vary from state to state, or country to country.

LENNTECH

info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289



3M and Betapure are a trademarks of 3M Company used under license.

For more contact addresses visit our website www.3M.eu/filtration or www.3Mpurification.com/international.

Data may be subject to change without further notice.

© 3M 2010. All rights reserved.

v.2 - DOC10061
LITCTBPAU1.EU - 1110

The below Cuno -series capsule filters are all the models that are potentially possible in all variations.

Please note that not all models are actually produced or on stock and some model numbers and names have become obsolete. Nevertheless this should help as cross reference table chart for Cuno filters nomenclature.

Betapure AU series

AUZ13020C01	AUB11C01
AUZ13020C02	AUB11C02
AUZ13030C01	AUC11C01
AUZ13030C02	AUC11C02
AUZ13050C01	AUE11C01
AUZ13050C02	AUE11C02
AUZ13060C01	AUG11C01
AUZ13060C02	AUG11C02
AUZ13070C01	AUL11C01
AUZ13070C02	AUL11C02
AUZ13080C01	AUQ11C01
AUZ13080C02	AUQ11C02
AUZ13100C01	AUV11C01
AUZ13100C02	AUV11C02
AUZ13120C01	AUW11C01
AUZ13120C02	AUW11C02
AUZ13150C01	AUX11C01
AUZ13150C02	AUX11C02

Lenntech B.V.
T +31-15-261.09.00
F +31-15-261.62.89
info@lenntech.com
www.lenntech.com

Rotterdamseweg 402

2629HH Delft

Netherlands

The below Cuno -series cartridge filters are all the models that are potentially possible in all variations.
Please note that not all models are actually produced or on stock and some model numbers and names have become obsolete.
Nevertheless this should help as cross reference table chart for Cuno filters nomenclature.

Betapure AU series

AU09B11	AU29B11	AU09B12	AU29B12
AU09C11	AU29C11	AU09C12	AU29C12
AU09E11	AU29E11	AU09E12	AU29E12
AU09G11	AU29G11	AU09G12	AU29G12
AU09L11	AU29L11	AU09L12	AU29L12
AU09Q11	AU29Q11	AU09Q12	AU29Q12
AU09V11	AU29V11	AU09V12	AU29V12
AU09W11	AU29W11	AU09W12	AU29W12
AU09X11	AU29X11	AU09X12	AU29X12
AU10B11	AU30B11	AU10B12	AU30B12
AU10C11	AU30C11	AU10C12	AU30C12
AU10E11	AU30E11	AU10E12	AU30E12
AU10G11	AU30G11	AU10G12	AU30G12
AU10L11	AU30L11	AU10L12	AU30L12
AU10Q11	AU30Q11	AU10Q12	AU30Q12
AU10V11	AU30V11	AU10V12	AU30V12
AU10W11	AU30W11	AU10W12	AU30W12
AU10X11	AU30X11	AU10X12	AU30X12
AU19B11	AU39B11	AU19B12	AU39B12
AU19C11	AU39C11	AU19C12	AU39C12
AU19E11	AU39E11	AU19E12	AU39E12
AU19G11	AU39G11	AU19G12	AU39G12
AU19L11	AU39L11	AU19L12	AU39L12
AU19Q11	AU39Q11	AU19Q12	AU39Q12
AU19V11	AU39V11	AU19V12	AU39V12
AU19W11	AU39W11	AU19W12	AU39W12
AU19X11	AU39X11	AU19X12	AU39X12
AU20B11	AU40B11	AU20B12	AU40B12
AU20C11	AU40C11	AU20C12	AU40C12
AU20E11	AU40E11	AU20E12	AU40E12
AU20G11	AU40G11	AU20G12	AU40G12
AU20L11	AU40L11	AU20L12	AU40L12
AU20Q11	AU40Q11	AU20Q12	AU40Q12
AU20V11	AU40V11	AU20V12	AU40V12
AU20W11	AU40W11	AU20W12	AU40W12
AU20X11	AU40X11	AU20X12	AU40X12

Lenntech B.V.
T +31-15-261.09.00
F +31-15-261.62.89
info@lenntech.com
www.lenntech.com

Rotterdamseweg 402 2629HH Delft Netherlands

The below Cuno -series cartridge filters are all the models that are potentially possible in all variations.
 Please note that not all models are actually produced or on stock and some model numbers and names have become obsolete.
 Nevertheless this should help as cross reference table chart for Cuno filters nomenclature.

Betapure AU Z series

AU09Z13BA020	AU10Z13BA020	AU19Z13BA020	AU20Z13BA020	AU29Z13BA020	AU30Z13BA020	AU09Z13BA020	AU09Z13BA020	AU40Z11FA060
AU09Z13BA030	AU10Z13BA030	AU19Z13BA030	AU20Z13BA030	AU29Z13BA030	AU30Z13BA030	AU09Z13BA030	AU09Z13BA030	AU40Z11FA070
AU09Z13BA050	AU10Z13BA050	AU19Z13BA050	AU20Z13BA050	AU29Z13BA050	AU30Z13BA050	AU09Z13BA050	AU09Z13BA050	AU40Z11FA080
AU09Z13BB020	AU10Z13BB020	AU19Z13BB020	AU20Z13BB020	AU29Z13BB020	AU30Z13BB020	AU09Z13BB020	AU09Z13BB020	AU40Z11FA100
AU09Z13BB030	AU10Z13BB030	AU19Z13BB030	AU20Z13BB030	AU29Z13BB030	AU30Z13BB030	AU39Z13BB030	AU40Z13BB030	AU40Z11FA120
AU09Z13BB050	AU10Z13BB050	AU19Z13BB050	AU20Z13BB050	AU29Z13BB050	AU30Z13BB050	AU39Z13BB050	AU40Z13BB050	AU40Z11FA150
AU09Z13BC020	AU10Z13BC020	AU19Z13BC020	AU20Z13BC020	AU29Z13BC020	AU30Z13BC020	AU39Z13BC020	AU40Z13BC020	AU40Z11FB060
AU09Z13BC030	AU10Z13BC030	AU19Z13BC030	AU20Z13BC030	AU29Z13BC030	AU30Z13BC030	AU39Z13BC030	AU40Z13BC030	AU40Z11FB070
AU09Z13BC050	AU10Z13BC050	AU19Z13BC050	AU20Z13BC050	AU29Z13BC050	AU30Z13BC050	AU39Z13BC050	AU40Z13BC050	AU40Z11FB080
AU09Z13BD020	AU10Z13BD020	AU19Z13BD020	AU20Z13BD020	AU29Z13BD020	AU30Z13BD020	AU39Z13BD020	AU40Z13BD020	AU40Z11FB100
AU09Z13BD030	AU10Z13BD030	AU19Z13BD030	AU20Z13BD030	AU29Z13BD030	AU30Z13BD030	AU39Z13BD030	AU40Z13BD030	AU40Z11FB120
AU09Z13BD050	AU10Z13BD050	AU19Z13BD050	AU20Z13BD050	AU29Z13BD050	AU30Z13BD050	AU39Z13BD050	AU40Z13BD050	AU40Z11FB150
AU09Z13CA020	AU10Z13CA020	AU19Z13CA020	AU20Z13CA020	AU29Z13CA020	AU30Z13CA020	AU39Z13CA020	AU40Z13CA020	AU40Z11FC060
AU09Z13CA030	AU10Z13CA030	AU19Z13CA030	AU20Z13CA030	AU29Z13CA030	AU30Z13CA030	AU39Z13CA030	AU40Z13CA030	AU40Z11FC070
AU09Z13CA050	AU10Z13CA050	AU19Z13CA050	AU20Z13CA050	AU29Z13CA050	AU30Z13CA050	AU39Z13CA050	AU40Z13CA050	AU40Z11FC080
AU09Z13CB020	AU10Z13CB020	AU19Z13CB020	AU20Z13CB020	AU29Z13CB020	AU30Z13CB020	AU39Z13CB020	AU40Z13CB020	AU40Z11FC100
AU09Z13CB030	AU10Z13CB030	AU19Z13CB030	AU20Z13CB030	AU29Z13CB030	AU30Z13CB030	AU39Z13CB030	AU40Z13CB030	AU40Z11FC120
AU09Z13CB050	AU10Z13CB050	AU19Z13CB050	AU20Z13CB050	AU29Z13CB050	AU30Z13CB050	AU39Z13CB050	AU40Z13CB050	AU40Z11FC150
AU09Z13CC020	AU10Z13CC020	AU19Z13CC020	AU20Z13CC020	AU29Z13CC020	AU30Z13CC020	AU39Z13CC020	AU40Z13CC020	AU40Z11FD060
AU09Z13CC030	AU10Z13CC030	AU19Z13CC030	AU20Z13CC030	AU29Z13CC030	AU30Z13CC030	AU39Z13CC030	AU40Z13CC030	AU40Z11FD070
AU09Z13CC050	AU10Z13CC050	AU19Z13CC050	AU20Z13CC050	AU29Z13CC050	AU30Z13CC050	AU39Z13CC050	AU40Z13CC050	AU40Z11FD080
AU09Z13CD020	AU10Z13CD020	AU19Z13CD020	AU20Z13CD020	AU29Z13CD020	AU30Z13CD020	AU39Z13CD020	AU40Z13CD020	AU40Z11FD100
AU09Z13CD030	AU10Z13CD030	AU19Z13CD030	AU20Z13CD030	AU29Z13CD030	AU30Z13CD030	AU39Z13CD030	AU40Z13CD030	AU40Z11FD120
AU09Z13CD050	AU10Z13CD050	AU19Z13CD050	AU20Z13CD050	AU29Z13CD050	AU30Z13CD050	AU39Z13CD050	AU40Z13CD050	AU40Z11FD150
AU09Z13DA020	AU10Z13DA020	AU19Z13DA020	AU20Z13DA020	AU29Z13DA020	AU30Z13DA020	AU39Z13DA020	AU40Z13DA020	AU39Z11FA060
AU09Z13DA030	AU10Z13DA030	AU19Z13DA030	AU20Z13DA030	AU29Z13DA030	AU30Z13DA030	AU39Z13DA030	AU40Z13DA030	AU39Z11FA070
AU09Z13DA050	AU10Z13DA050	AU19Z13DA050	AU20Z13DA050	AU29Z13DA050	AU30Z13DA050	AU39Z13DA050	AU40Z13DA050	AU39Z11FA080
AU09Z13DB020	AU10Z13DB020	AU19Z13DB020	AU20Z13DB020	AU29Z13DB020	AU30Z13DB020	AU39Z13DB020	AU40Z13DB020	AU39Z11FA100
AU09Z13DB030	AU10Z13DB030	AU19Z13DB030	AU20Z13DB030	AU29Z13DB030	AU30Z13DB030	AU39Z13DB030	AU40Z13DB030	AU39Z11FA120
AU09Z13DB050	AU10Z13DB050	AU19Z13DB050	AU20Z13DB050	AU29Z13DB050	AU30Z13DB050	AU39Z13DB050	AU40Z13DB050	AU39Z11FA150
AU09Z13DC020	AU10Z13DC020	AU19Z13DC020	AU20Z13DC020	AU29Z13DC020	AU30Z13DC020	AU39Z13DC020	AU40Z13DC020	AU39Z11FB060
AU09Z13DC030	AU10Z13DC030	AU19Z13DC030	AU20Z13DC030	AU29Z13DC030	AU30Z13DC030	AU39Z13DC030	AU40Z13DC030	AU39Z11FB070
AU09Z13DC050	AU10Z13DC050	AU19Z13DC050	AU20Z13DC050	AU29Z13DC050	AU30Z13DC050	AU39Z13DC050	AU40Z13DC050	AU39Z11FB080
AU09Z13DD020	AU10Z13DD020	AU19Z13DD020	AU20Z13DD020	AU29Z13DD020	AU30Z13DD020	AU39Z13DD020	AU40Z13DD020	AU39Z11FB100
AU09Z13DD030	AU10Z13DD030	AU19Z13DD030	AU20Z13DD030	AU29Z13DD030	AU30Z13DD030	AU39Z13DD030	AU40Z13DD030	AU39Z11FB120
AU09Z13DD050	AU10Z13DD050	AU19Z13DD050	AU20Z13DD050	AU29Z13DD050	AU30Z13DD050	AU39Z13DD050	AU40Z13DD050	AU39Z11FB150
AU09Z13EA020	AU10Z13EA020	AU19Z13EA020	AU20Z13EA020	AU29Z13EA020	AU30Z13EA020	AU39Z13EA020	AU40Z13EA020	AU39Z11FC060
AU09Z13EA030	AU10Z13EA030	AU19Z13EA030	AU20Z13EA030	AU29Z13EA030	AU30Z13EA030	AU39Z13EA030	AU40Z13EA030	AU39Z11FC070
AU09Z13EA050	AU10Z13EA050	AU19Z13EA050	AU20Z13EA050	AU29Z13EA050	AU30Z13EA050	AU39Z13EA050	AU40Z13EA050	AU39Z11FC080
AU09Z13EB020	AU10Z13EB020	AU19Z13EB020	AU20Z13EB020	AU29Z13EB020	AU30Z13EB020	AU39Z13EB020	AU40Z13EB020	AU39Z11FC100
AU09Z13EB030	AU10Z13EB030	AU19Z13EB030	AU20Z13EB030	AU29Z13EB030	AU30Z13EB030	AU39Z13EB030	AU40Z13EB030	AU39Z11FC120
AU09Z13EB050	AU10Z13EB050	AU19Z13EB050	AU20Z13EB050	AU29Z13EB050	AU30Z13EB050	AU39Z13EB050	AU40Z13EB050	AU39Z11FC150
AU09Z13EC020	AU10Z13EC020	AU19Z13EC020	AU20Z13EC020	AU29Z13EC020	AU30Z13EC020	AU39Z13EC020	AU40Z13EC020	AU39Z11FD060
AU09Z13EC030	AU10Z13EC030	AU19Z13EC030	AU20Z13EC030	AU29Z13EC030	AU30Z13EC030	AU39Z13EC030	AU40Z13EC030	AU39Z11FD070
AU09Z13EC050	AU10Z13EC050	AU19Z13EC050	AU20Z13EC050	AU29Z13EC050	AU30Z13EC050	AU39Z13EC050	AU40Z13EC050	AU39Z11FD080
AU09Z13ED020	AU10Z13ED020	AU19Z13ED020	AU20Z13ED020	AU29Z13ED020	AU30Z13ED020	AU39Z13ED020	AU40Z13ED020	AU39Z11FD100
AU09Z13ED030	AU10Z13ED030	AU19Z13ED030	AU20Z13ED030	AU29Z13ED030	AU30Z13ED030	AU39Z13ED030	AU40Z13ED030	AU39Z11FD120
AU09Z13ED050	AU10Z13ED050	AU19Z13ED050	AU20Z13ED050	AU29Z13ED050	AU30Z13ED050	AU39Z13ED050	AU40Z13ED050	AU39Z11FD150
AU09Z13FA020	AU10Z13FA020	AU19Z13FA020	AU20Z13FA020	AU29Z13FA020	AU30Z13FA020	AU39Z13FA020	AU40Z13FA020	AU30Z11FA060
AU09Z13FA030	AU10Z13FA030	AU19Z13FA030	AU20Z13FA030	AU29Z13FA030	AU30Z13FA030	AU39Z13FA030	AU40Z13FA030	AU30Z11FA070
AU09Z13FA050	AU10Z13FA050	AU19Z13FA050	AU20Z13FA050	AU29Z13FA050	AU30Z13FA050	AU39Z13FA050	AU40Z13FA050	AU30Z11FA080
AU09Z13FB020	AU10Z13FB020	AU19Z13FB020	AU20Z13FB020	AU29Z13FB020	AU30Z13FB020	AU39Z13FB020	AU40Z13FB020	AU30Z11FA100
AU09Z13FB030	AU10Z13FB030	AU19Z13FB030	AU20Z13FB030	AU29Z13FB030	AU30Z13FB030	AU39Z13FB030	AU40Z13FB030	AU30Z11FA120
AU09Z13FB050	AU10Z13FB050	AU19Z13FB050	AU20Z13FB050	AU29Z13FB050	AU30Z13FB050	AU39Z13FB050	AU40Z13FB050	AU30Z11FA150
AU09Z13FC020	AU10Z13FC020	AU19Z13FC020	AU20Z13FC020	AU29Z13FC020	AU30Z13FC020	AU39Z13FC020	AU40Z13FC020	AU30Z11FB060
AU09Z13FC030	AU10Z13FC030	AU19Z13FC030	AU20Z13FC030	AU29Z13FC030	AU30Z13FC030	AU39Z13FC030	AU40Z13FC030	AU30Z11FB070
AU09Z13FC050	AU10Z13FC050	AU19Z13FC050	AU20Z13FC050	AU29Z13FC050	AU30Z13FC050	AU39Z13FC050	AU40Z13FC050	AU30Z11FB080
AU09Z13FD020	AU10Z13FD020	AU19Z13FD020	AU20Z13FD020	AU29Z13FD020	AU30Z13FD020	AU39Z13FD020	AU40Z13FD020	AU30Z11FB100
AU09Z13FD030	AU10Z13FD030	AU19Z13FD030	AU20Z13FD030	AU29Z13FD030	AU30Z13FD030	AU39Z13FD030	AU40Z13FD030	AU30Z11FB120
AU09Z13FD050	AU10Z13FD050	AU19Z13FD050	AU20Z13FD050	AU29Z13FD050	AU30Z13FD050	AU39Z13FD050	AU40Z13FD050	AU30Z11FB150
AU09Z11BA060	AU10Z11BA060	AU19Z11BA060	AU20Z11BA060	AU29Z11BA060	AU30Z11BA060	AU39Z11BA060	AU40Z11BA060	AU30Z11FC060
AU09Z11BA070	AU10Z11BA070	AU19Z11BA070	AU20Z11BA070	AU29Z11BA070	AU30Z11BA070	AU39Z11BA070	AU40Z11BA070	AU30Z11FC070
AU09Z11BA080	AU10Z11BA080	AU19Z11BA080	AU20Z11BA080	AU29Z11BA080	AU30Z11BA080	AU39Z11BA080	AU40Z11BA080	AU30Z11FC080
AU09Z11BA100	AU10Z11BA100	AU19Z11BA100	AU20Z11BA100	AU29Z11BA100	AU30Z11BA100	AU39Z11BA100	AU40Z11BA100	AU30Z11FC100
AU09Z11BA120	AU10Z11BA120	AU19Z11BA120	AU20Z11BA120	AU29Z11BA120	AU30Z11BA120	AU39Z11BA120	AU40Z11BA120	AU30Z11FC120
AU09Z11BA150	AU10Z11BA150	AU19Z11BA150	AU20Z11BA150	AU29Z11BA150	AU30Z11BA150	AU39Z11BA150	AU40Z11BA150	AU30Z11FC150

AU09Z11EB060	AU10Z11EB060	AU19Z11EB060	AU20Z11EB060	AU29Z11EB060	AU30Z11EB060	AU39Z11EB060	AU40Z11EB060	AU19Z11FD060
AU09Z11EB070	AU10Z11EB070	AU19Z11EB070	AU20Z11EB070	AU29Z11EB070	AU30Z11EB070	AU39Z11EB070	AU40Z11EB070	AU19Z11FD070
AU09Z11EB080	AU10Z11EB080	AU19Z11EB080	AU20Z11EB080	AU29Z11EB080	AU30Z11EB080	AU39Z11EB080	AU40Z11EB080	AU19Z11FD080
AU09Z11EB100	AU10Z11EB100	AU19Z11EB100	AU20Z11EB100	AU29Z11EB100	AU30Z11EB100	AU39Z11EB100	AU40Z11EB100	AU19Z11FD100
AU09Z11EB120	AU10Z11EB120	AU19Z11EB120	AU20Z11EB120	AU29Z11EB120	AU30Z11EB120	AU39Z11EB120	AU40Z11EB120	AU19Z11FD120
AU09Z11EB150	AU10Z11EB150	AU19Z11EB150	AU20Z11EB150	AU29Z11EB150	AU30Z11EB150	AU39Z11EB150	AU40Z11EB150	AU19Z11FD150
AU09Z11EC060	AU10Z11EC060	AU19Z11EC060	AU20Z11EC060	AU29Z11EC060	AU30Z11EC060	AU39Z11EC060	AU40Z11EC060	AU10Z11FA060
AU09Z11EC070	AU10Z11EC070	AU19Z11EC070	AU20Z11EC070	AU29Z11EC070	AU30Z11EC070	AU39Z11EC070	AU40Z11EC070	AU10Z11FA070
AU09Z11EC080	AU10Z11EC080	AU19Z11EC080	AU20Z11EC080	AU29Z11EC080	AU30Z11EC080	AU39Z11EC080	AU40Z11EC080	AU10Z11FA080
AU09Z11EC100	AU10Z11EC100	AU19Z11EC100	AU20Z11EC100	AU29Z11EC100	AU30Z11EC100	AU39Z11EC100	AU40Z11EC100	AU10Z11FA100
AU09Z11EC120	AU10Z11EC120	AU19Z11EC120	AU20Z11EC120	AU29Z11EC120	AU30Z11EC120	AU39Z11EC120	AU40Z11EC120	AU10Z11FA120
AU09Z11EC150	AU10Z11EC150	AU19Z11EC150	AU20Z11EC150	AU29Z11EC150	AU30Z11EC150	AU39Z11EC150	AU40Z11EC150	AU10Z11FA150
AU09Z11ED060	AU10Z11ED060	AU19Z11ED060	AU20Z11ED060	AU29Z11ED060	AU30Z11ED060	AU39Z11ED060	AU40Z11ED060	AU10Z11FB060
AU09Z11ED070	AU10Z11ED070	AU19Z11ED070	AU20Z11ED070	AU29Z11ED070	AU30Z11ED070	AU39Z11ED070	AU40Z11ED070	AU10Z11FB070
AU09Z11ED080	AU10Z11ED080	AU19Z11ED080	AU20Z11ED080	AU29Z11ED080	AU30Z11ED080	AU39Z11ED080	AU40Z11ED080	AU10Z11FB080
AU09Z11ED100	AU10Z11ED100	AU19Z11ED100	AU20Z11ED100	AU29Z11ED100	AU30Z11ED100	AU39Z11ED100	AU40Z11ED100	AU10Z11FB100
AU09Z11ED120	AU10Z11ED120	AU19Z11ED120	AU20Z11ED120	AU29Z11ED120	AU30Z11ED120	AU39Z11ED120	AU40Z11ED120	AU10Z11FB120
AU09Z11ED150	AU10Z11ED150	AU19Z11ED150	AU20Z11ED150	AU29Z11ED150	AU30Z11ED150	AU39Z11ED150	AU40Z11ED150	AU10Z11FB150
AU09Z11FA060	AU10Z11FC060	AU10Z11FC100	AU10Z11FD060	AU10Z11FD100	AU09Z11FD100	AU09Z11FD060	AU09Z11FC100	AU09Z11FC060
AU09Z11FA070	AU10Z11FC070	AU10Z11FC120	AU10Z11FD070	AU10Z11FD120	AU09Z11FD120	AU09Z11FD070	AU09Z11FC120	AU09Z11FC070
AU09Z11FA080	AU10Z11FC080	AU10Z11FC150	AU10Z11FD080	AU10Z11FD150	AU09Z11FD150	AU09Z11FD080	AU09Z11FC150	AU09Z11FC080
AU09Z11FA100	AU09Z11FB150	AU09Z11FB120	AU09Z11FB100	AU09Z11FB080	AU09Z11FB070	AU09Z11FB060	AU09Z11FA150	AU09Z11FA120

Lenntech B.V.
T +31-15-261.09.00
F +31-15-261.62.89
info@lenntech.com
www.lenntech.com

Rotterdamseweg 402

2629HH Delft

Netherlands