

FilmTec™ Membranes

FilmTec™ 4.6" Tapwater RO Elements

Description


FilmTec™ 4.6-inch diameter RO elements offer high quality water for sanitary applications, using the high performance TW30HP membrane, which offers excellent permeate flow and salt rejection. These elements are made with the same high quality materials of construction as our larger FilmTec™ Elements used in municipal and industrial systems. For added convenience during shipping, storage and loading, these elements are available as either wet or dry products.

Typical Properties

| FilmTec™ Element | Product Water Flow Rate | | | Applied Pressure | Stabilized Salt |
|------------------|-------------------------|---------------------|-------|------------------|-------------------|
| | (gpd) | (m ³ /d) | (l/h) | psig (bar) | Rejection Cl- (%) |
| TW30HP-4611 | 1,200 | 4.54 | 189 | 225 (15.5) | 99.0 |
| TW30HP-4619 | 1,450 | 5.49 | 229 | 225 (15.5) | 99.0 |
| TW30HP-4641 | 5,200 | 19.68 | 820 | 225 (15.5) | 99.0 |

1. Permeate flow and salt rejection based on the following test conditions: 2,000 ppm NaCl, pressure specified above, 77°F (25°C), pH 8 and the following recovery rates; TW30HP-4611 - 5%, TW30HP-4619 - 8%, TW30HP-4641 - 15%.
2. Minimum salt rejection for individual element is 98.0%.
3. Flow rates for individual elements may vary +/-20%.
4. For the purpose of improvement, specifications may be updated periodically.

Element Dimensions



| FilmTec™ Element | Maximum Feed | Dimensions – Inches (mm) | | | |
|------------------|-----------------------------------|--------------------------|-----------|-----------|------------|
| | Flow Rate, gpm (m ³ h) | A | B | C | D |
| TW30HP-4611 | 18 (4.1) | 11.32 (287.53) | -- | 0.75 (19) | 4.61 (117) |
| TW30HP-4619 | 18 (4.1) | 19.20 (487.68) | -- | 0.75 (19) | 4.61 (117) |
| TW30HP-4641 | 18 (4.1) | 41.31 (1,049) | 2.19 (56) | 0.75 (19) | 4.61 (117) |

1. Refer to WAVE for multiple-element systems using the TW30HP-4641. 1 inch = 25.4 mm
2. Elements fit nominal 4.6-inch I.D. pressure vessels.

Operating and Cleaning Limits

| | |
|--------------------------------------|-------------------------------|
| Membrane Type | Polyamide Thin-Film Composite |
| Maximum Operating Temperature | 113°F (45°C) |
| Maximum Operating Pressure | 600 psi (4.1 MPa) |
| Maximum Pressure Drop | 15 psi (1.0 bar) |
| pH Range | |
| Continuous Operation ^a | 2 - 11 |
| Short-Term Cleaning ^b | 1 - 13 |
| Maximum Feed Silt Density Index | 5 |
| Free Chlorine Tolerance ^c | <0.1 ppm |

- Maximum temperature for continuous operation above pH 10 is 95°F (35°C)
- Refer to [Cleaning Guidelines](#) (Form No. 45-D01696-en).
- Under certain conditions, the presence of free chlorine and other oxidizing agents will cause premature membrane failure. Since oxidation damage is not covered under warranty, DW&PS recommends removing residual free chlorine by pretreatment prior to membrane exposure. Please refer to [FilmTec™ Design Guidelines for multiple-element systems of 8-inch elements](#) (Form No. 45-D01695-en) for more information.

Important Operating Information

- Keep elements moist at all times after initial wetting.
- If operating specifications given in this Product Information bulletin are not strictly followed, the [FilmTec™ Reverse Osmosis and Nanofiltration Three-Year Prorated Limited Warranty](#) (Form No. 45-D00903-en) will be null and void.
- To prevent biological growth during storage, shipping or system shutdowns it is recommended that FilmTec™ Elements be immersed in a protective solution. The standard storage solution contains 1.0 percent (by weight) sodium metabisulfite (food grade).
- The customer is fully responsible for the effects of incompatible chemicals on elements. Their use will void the [FilmTec™ Reverse Osmosis and Nanofiltration Three-Year Prorated Limited Warranty](#) (Form No. 45-D00903-en).

Product Stewardship

DuPont has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with DuPont products—from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

DuPont strongly encourages its customers to review both their manufacturing processes and their applications of DuPont products from the standpoint of human health and environmental quality to ensure that DuPont products are not used in ways for which they are not intended or tested. DuPont personnel are available to answer your questions and to provide reasonable technical support. DuPont product literature, including safety data sheets, should be consulted prior to use of DuPont products. Current safety data sheets are available from DuPont.

Please be aware of the following:

- The use of this product in and of itself does not necessarily guarantee the removal of cysts and pathogens from water. Effective cyst and pathogen reduction is dependent on the complete system design and on the operation and maintenance of the system.
- Permeate obtained from the first hour of operation should be discarded.



info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289

Have a question? Contact us at:

All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, ℠ or ® are owned by affiliates of DuPont de Nemours Inc. unless otherwise noted. © 2020 DuPont.

