



HYDRACoRe70pHT Series

High flux, 720 Dalton MWCO thinfilm, chlorine-resistant nanofiltration membranes designed specifically for color removal as well as acid, caustic, and other chemical reclamation applications through the membrane's ability to reject color, proteins, fats, oils, and other macromolecular species.

Products & Guidelines:

Model	Feed Spacer, inches (cm)	Area, ft2 (m2)	Dimens	ions, inch	nes. (cm)	Feed Flow, GPM (m3/hr)	Max. Pressure Drop per Element, psi (bar)
HYDRACoRe70pHT 4040-46	0.046 (0.12)	70 (6.4)	40.0 (102)	3.98 (10.1)	0.75 (1.9)OD	30 (6.8)	15 (1.0)
HYDRACoRe70pHT 8040-46	0.046 (0.12)	275 (25)	40.0 (102)	7.90 (20.1)	1.125 (2.9)ID	80 (18.2)	15 (1.0)

Type Configuration: Sanitary Spiral Wound Membrane Polymer: Sulfonated Polyethersulfone

Application Data Maximum Applied Pressure:

600 psig (bar) 10 PPM Maximum Continuous Chlorine Concentration¹: Maximum Chlorine Concentration for Cleaning¹: 100 PPM Maximum Operating Temperature: 158 (70 °C) Operating pH Range: 1 - 13.5

Cleaning pH Range: 1 - 13.5 Maximum Pressure Drop for a vessel 60 psi (4 bar)

4040 Style



¹ Transition metals (Fe, Mn) should not be present in the water or on the membrane as these can accelerate detrimental reactions between the membrane and the oxidant.

Notice: Elements include interconnector assembly, ATDs and brine seals. Elements are enclosed in a sealed polyethylene bag containing less than 1.0% sodium meta-bisulfite solution, and then packaged in a cardboard box. Hydranautics believes the information and data contained herein to be accurate and useful. The information and data are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. Hydranautics assumes no liability for results obtained or damages incurred through the application of the presented information and data. It is the user's responsibility to determine the appropriateness of Hydranautics' products for the user's specific end uses.



www.lenntech.com

info@lenntech.com Fax. +31-15-261.62.89

Tel. +31-15-261.09.00