

| Part Number | Model Name / Description | Type | Flow | | Length (A) | | OUTPUT O.D. (B) | | FEED O.D. (C) | | Average NaCl rejection | Minimum NaCl rejection | Average MgSO4 rejection | Minimum MgSO4 rejection | Shipping Weight | | Membrane Active Area | | Max. Pressure | | Max. Temperature | |
|-------------------|--------------------------|-------|------|---------------------|------------|------|-----------------|-------|---------------|------|------------------------|------------------------|-------------------------|-------------------------|-----------------|------|----------------------|------|-----------------|----------------|------------------|-----|
| | | | gpd | m ³ /day | inch | cm | inch | cm | inch | cm | inch | cm | % | % | % | % | lbs | kg | ft ² | m ² | psi | KPa |
| ESPA1 | Saving Energy | 12000 | 45.2 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.3 | 99.0 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| ESPA-2514 | Saving Energy | 250 | 0.9 | 14 | 35.6 | 2.4 | 6.10 | 0.75 | 1.9 | 99.4 | 98.0 | | | 1.0 | 0.5 | 5 | 0.5 | 300 | 20.68 | 113 | 45.0 | |
| ESPA-2521 | Saving Energy | 350 | 1.3 | 21 | 53.3 | 2.4 | 6.10 | 0.75 | 1.9 | 99.4 | 98.0 | | | 2.0 | 0.9 | 9.9 | 0.9 | 300 | 20.68 | 113 | 45.0 | |
| ESPA-2540 | Saving Energy | 750 | 2.8 | 40 | 101.6 | 2.4 | 6.10 | 0.75 | 1.9 | 99.4 | 98.0 | | | 4.0 | 1.8 | 25.5 | 2.4 | 300 | 20.68 | 113 | 45.0 | |
| ESPA-4014 | Saving Energy | 500 | 1.9 | 14 | 35.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.4 | 98.0 | | | 3.1 | 1.4 | 16.9 | 1.6 | 300 | 20.68 | 113 | 45.0 | |
| ESPA-4021 | Saving Energy | 1000 | 3.8 | 21 | 53.3 | 3.95 | 10.03 | 0.75 | 1.9 | 99.4 | 98.0 | | | 4.0 | 1.8 | 29 | 2.7 | 300 | 20.68 | 113 | 45.0 | |
| ESPA-4611 | Saving Energy | 930 | 3.5 | 11.3 | 28.7 | 4.6 | 11.68 | 0.75 | 1.9 | 99.4 | 98.0 | | | 11.0 | 5.0 | 31 | 2.9 | 300 | 20.68 | 113 | 45.0 | |
| ESPA-4641 | Saving Energy | 3600 | 13.6 | 41.3 | 104.9 | 4.6 | 11.68 | 0.75 | 1.91 | 99.4 | 97.5 | | | 11.0 | 5.0 | 120 | 11.1 | 300 | 20.68 | 113 | 45.0 | |
| ESPA-50 | Saving Energy | 50 | 0.2 | 11.74 | 29.8 | 1.78 | 4.52 | 0.68 | 1.7 | 99.0 | | | | 0.5 | 0.23 | | | 300 | 20.68 | 113 | 45.0 | |
| ESPA-75 | Saving Energy | 75 | 0.3 | 11.74 | 29.8 | 1.78 | 4.52 | 0.68 | 1.7 | 98.0 | | | | 0.5 | 0.23 | | | 300 | 20.68 | 113 | 45.0 | |
| ESPA1-2012 | Saving Energy | | | | | | | | | | | | | | | | | | | | | |
| ESPA1-2521 | Saving Energy | 350 | 1.3 | 21 | 53.3 | 2.4 | 6.1 | 0.75 | 1.9 | 99.4 | 98.0 | | | 2.0 | 0.9 | 10 | 0.9 | 300 | 20.68 | 113 | 45.0 | |
| ESPA1-4014 | Saving Energy | 500 | 1.9 | 14 | 35.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.4 | 98.0 | | | 3.1 | 1.4 | 17 | 1.6 | 300 | 20.68 | 113 | 45.0 | |
| ESPA1-4040 | Saving Energy | 2600 | 9.8 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.3 | 99.0 | | | 7.9 | 3.6 | 85 | 7.9 | 600 | 41.37 | 113 | 45.0 | |
| ESPA1-8040 | Saving Energy | 12000 | 45.2 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.3 | 99.0 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| ESPA2-4040 | Saving Energy | 1900 | 7.2 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.6 | 99.4 | | | 7.9 | 3.6 | 85 | 7.9 | 600 | 41.37 | 113 | 45.0 | |
| ESPA2-LD-4040 | Saving Energy | 2000 | 7.5 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.6 | 99.4 | | | 7.9 | 3.6 | 80 | 7.4 | 600 | 41.37 | 113 | 45.0 | |
| ESPA2-LD | Saving Energy | 10000 | 37.7 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.6 | 99.4 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| ESPA2-8040 | Saving Energy | 9000 | 33.9 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.6 | 99.5 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| ESPA2-MAX-8040 | Saving Energy | 12000 | 45.2 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.6 | 99.5 | | | 36.2 | 16.4 | 440 | 40.8 | 600 | 41.37 | 113 | 45.0 | |
| ESPA3-4040 | Saving Energy | 3000 | 11.3 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 98.5 | | | | 5.1 | 2.3 | 85 | 7.9 | 600 | 41.37 | 113 | 45.0 | |
| ESPA3-8040 | Saving Energy | | | | | | | | 0.0 | | | | | | | | | | | | | |
| ESPA4-4040 | Saving Energy | 2500 | 9.4 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.2 | 99.0 | | | 7.9 | 3.6 | 85 | 7.9 | 600 | 41.37 | 113 | 45.0 | |
| ESPA4-8040 | Saving Energy | 12000 | 45.2 | 40 | 101.6 | 3.95 | 10.03 | 1.125 | 2.9 | 99.2 | 99.0 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| ESPA4-LD | Saving Energy | 12000 | 45.2 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.2 | 99.0 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| ESPA4-MAX | Saving Energy | 13200 | 49.7 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.2 | 99.0 | | | 36.2 | 16.4 | 440 | 40.8 | 600 | 41.37 | 113 | 45.0 | |
| ESPAB-MAX | Saving Energy | 9000 | 33.9 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.3 | 99.0 | | | 36.2 | 16.4 | 440 | 40.8 | 600 | 41.37 | 113 | 45.0 | |
| ESPAUP-8040 | Saving Energy | | | | | | | | | | | | | | | | | | | | | |
| CPA2 | High Rejection | 10000 | 37.7 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.5 | | | 36.2 | 16.4 | 365 | 33.9 | 600 | 41.37 | 113 | 45.0 | |
| CPA2-4040 | High Rejection | 2250 | 8.5 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.5 | 99.2 | | | 7.9 | 3.6 | 85 | 7.9 | 600 | 41.37 | 113 | 45.0 | |
| CPA2-8040 | High Rejection | 10000 | 37.7 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.5 | | | 36.2 | 16.4 | 365 | 33.9 | 600 | 41.37 | 113 | 45.0 | |
| CPA3 | High Rejection | 11000 | 41.4 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.6 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| CPA3-8040 | High Rejection | 11000 | 41.4 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.6 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| CPA3-LD-8040 | High Rejection | 11000 | 41.4 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.6 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| CPA4-8040 | High Rejection | 11000 | 41.4 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.6 | | | 36.2 | 16.4 | | | | | | | |
| CPA5-LD | High Rejection | 11000 | 41.4 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.6 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| CPA5-LD-4040 | High Rejection | 2100 | 7.9 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.7 | 99.5 | | | 7.9 | 3.6 | 80 | 7.4 | 600 | 41.37 | 113 | 45.0 | |
| CPA5-LD-8040 | High Rejection | 11000 | 41.4 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.6 | | | 36.2 | 16.4 | | | | | | | |
| CPA5-MAX | High Rejection | 12000 | 45.2 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.6 | | | 36.2 | 16.4 | 440 | 40.8 | 600 | 41.37 | 113 | 45.0 | |
| CPA5-MAX-8040 | High Rejection | 12000 | 45.2 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.6 | | | 36.2 | 16.4 | 440 | 40.8 | 600 | 41.37 | 113 | 45.0 | |
| LFC1 | Low Fouling | 10000 | 37.7 | 40 | 101.6 | | 0.00 | | 0.0 | | 99.0 | | | | | 365 | 33.9 | 600 | 41.37 | 113 | 45.0 | |
| LFC3-LD | Low Fouling | 11000 | 41.4 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.5 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| LFC3-LD-4040 | Low Fouling | 2100 | 7.9 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.7 | 99.5 | | | 7.9 | 3.6 | 80 | 7.4 | 600 | 41.37 | 113 | 45.0 | |
| LFC3-LD-8040 | Low Fouling | 11000 | 41.4 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.5 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| LFC2 | Low Fouling | 11000 | 41.4 | 40 | 101.6 | | | | | | 95.0 | | | | | 365 | 33.9 | 600 | 41.37 | 113 | 45.0 | |
| LFC1-4040 | Low Fouling | 2300 | 8.7 | 40 | 101.6 | | | | | | 99.0 | | | 7.9 | 3.6 | 85 | 7.9 | 600 | 41.37 | 113 | 45.0 | |
| LFC2-4040 | Low Fouling | 2500 | 9.4 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | | 95.0 | | | 7.9 | 3.6 | 85 | 7.9 | 600 | 41.37 | 113 | 45.0 | |
| LFC1-8040 | Low Fouling | | | | | | | | | | | | | | | | | | | | | |
| LFC2-8040 | Low Fouling | | | | | | | | | | | | | | | | | | | | | |
| ESNA1-4040 | NanoFiltration | | | | | | | | | | | | | | | | | | | | | |
| ESNA1-LF | NanoFiltration | | | | | | | | | | | | | | | | | | | | | |
| ESNA1-LF2 | NanoFiltration | | | | | | | | | | | | | | | | | | | | | |
| ESNA1-LF2-LD-8040 | NanoFiltration | 10500 | 39.6 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 86.0 | 83.0 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| ESNA1-LF2-8040 | NanoFiltration | | | | | | | | | | | | | | | | 0.0 | 0.00 | | | | 0.0 |
| ESNA1-LF-LD | NanoFiltration | 8200 | 30.9 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 89.0 | 86.0 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| ESNA1-LF2-LD | NanoFiltration | 10500 | 39.6 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 86.0 | 83.0 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| NANO-BW | NanoFiltration | 11000 | 41.4 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.5 | | | 36.2 | 16.4 | 400 | 37.1 | 600 | 41.37 | 113 | 45.0 | |
| NANO-BW-MAX | NanoFiltration | 12000 | 45.2 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.7 | 99.5 | | | 36.2 | 16.4 | 440 | 40.8 | 600 | 41.37 | 113 | 45.0 | |
| NANO-SW | NanoFiltration | 11000 | 41.4 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.8 | 99.6 | | | 36.2 | 16.4 | 400 | 37.1 | 1200 | 82.74 | 113 | 45.0 | |
| SanRO HS 4040 | Sanitizable | 2200 | 8.3 | 40 | 101.6 | 3.98 | 10.11 | 0.75 | 1.9 | 99.7 | | | | 18.3 | 8.3 | 90 | 8.3 | 600 | 41.37 | 113 | 45.0 | |
| SanRO HS 8040 | Sanitizable | 8800 | 33.2 | 40 | 101.6 | 3.98 | 10.11 | 0.75 | 1.9 | 99.7 | | | | 18.3 | 8.3 | 380 | 35.2 | 600 | 41.37 | 113 | 45.0 | |
| SanRO HS2 4040 | Sanitizable | 3000 | 11.3 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | 96.4 | | | | 77.6 | 35.2 | 90 | 8.3 | 600 | 41.37 | 113 | 45.0 | |
| SanRO HS2 8040 | Sanitizable | 14000 | 52.8 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | 96.4 | | | | 77.6 | 35.2 | 380 | 35.2 | 600 | 41.37 | 113 | 45.0 | |
| SanRO ESPA2 4040 | Sanitizable | 3300 | 12.4 | 40 | 101.6 | 3.98 | 10.11 | 0.75 | 1.9 | 99.5 | | | | 18.3 | 8.3 | | | | | | | |
| SanRO CPA3 4040 | Sanitizable | 2600 | 9.8 | 40 | 101.6 | 3.98 | 10.11 | 0.75 | 1.9 | 99.6 | | | | 18.3 | 8.3 | | | | | | | |
| SanRO LFC3 4040 | Sanitizable | 2300 | 8.7 | 40 | 101.6 | 3.98 | 10.11 | 0.75 | 1.9 | 99.6 | | | | 18.3 | 8.3 | | | | | | | |

| Part Number | Model Name / Description | Type | Flow | | Length (A) | | OUTPUT O.D. (B) | | FEED O.D. (C) | | Average NaCl rejection | Minimum NaCl rejection | Average MgSO4 rejection | Minimum MgSO4 rejection | Shipping Weight | | Membrane Active Area | | Max. Pressure | | Max. Temperature | |
|-------------------------------------|--------------------------|-------------|-------|----------------------|------------|-------|-----------------|-------|---------------|-----|------------------------|------------------------|-------------------------|-------------------------|-----------------|------|----------------------|------|-----------------|----------------|------------------|------|
| | | | gpd | m ³ / day | inch | cm | inch | cm | inch | cm | inch | cm | % | % | % | % | lbs | kg | ft ² | m ² | psi | KPa |
| SanRO CPA4 4040 | | Sanitizable | 1400 | 5.3 | 40 | 101.6 | 3.98 | 10.11 | 0.75 | 1.9 | 99.6 | | | | 18.3 | 8.3 | | | | | | |
| SanRO ESPA2 8040 | | Sanitizable | 13000 | 49.0 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | 99.5 | | | | 77.6 | 35.2 | | | | | | |
| SanRO CPA3 8040 | | Sanitizable | 10500 | 39.6 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | 99.6 | | | | 77.6 | 35.2 | | | | | | |
| SanRO LFC3 8040 | | Sanitizable | 9000 | 33.9 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | 99.6 | | | | 77.6 | 35.2 | | | | | | |
| SanRO CPA4 8040 | | Sanitizable | 5500 | 20.7 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | 99.6 | | | | 77.6 | 35.2 | | | | | | |
| DairyUF 5K 3838-30 | | Sanitizable | 1805 | 6.8 | 38 | 96.5 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | | 80 | 7.4 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 5K 3838-46 | | Sanitizable | 1805 | 6.8 | 38 | 96.5 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | | 60 | 5.6 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 5K 4336-30 | | Sanitizable | 2097 | 7.9 | 35.5 | 90.2 | 4.28 | 10.87 | 0.83 | 2.1 | | | | | 0.0 | | 90 | 8.3 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 5K 4336-46 | | Sanitizable | 2097 | 7.9 | 35.5 | 90.2 | 4.28 | 10.87 | 0.83 | 2.1 | | | | | 0.0 | | 70 | 6.5 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 5K 6338-30 | | Sanitizable | 4195 | 15.8 | 38 | 96.5 | 6.36 | 16.15 | 1.138 | 2.9 | | | | | 0.0 | | 200 | 18.5 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 5K 6338-46 | | Sanitizable | 4195 | 15.8 | 38 | 96.5 | 6.36 | 16.15 | 1.138 | 2.9 | | | | | 0.0 | | 150 | 13.9 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 5K 8038-30 | | Sanitizable | 4832 | 18.2 | 38 | 96.5 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | | 360 | 33.4 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 5K 8038-46 | | Sanitizable | 4832 | 18.2 | 38 | 96.5 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | | 280 | 26.0 | 150 | 10.34 | 131 | 52.2 |
| DairyRO 3838-30 | | Sanitizable | 1805 | 6.8 | 38 | 96.5 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | | 80 | 7.4 | 800 | 55.16 | 122 | 48.6 |
| DairyRO 3838-46 | | Sanitizable | 1805 | 6.8 | 38 | 96.5 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | | 60 | 5.6 | 800 | 55.16 | 122 | 48.6 |
| DairyRO 3840-30 | | Sanitizable | 1805 | 6.8 | 38.75 | 98.4 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | | 80 | 7.4 | 800 | 55.16 | 122 | 48.6 |
| DairyRO 8038-30 | | Sanitizable | 4832 | 18.2 | 38 | 96.5 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | | 360 | 33.4 | 800 | 55.16 | 122 | 48.6 |
| DairyRO 8040-30 | | Sanitizable | 4832 | 18.2 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | | 360 | 33.4 | 800 | 55.16 | 122 | 48.6 |
| Hydrapolish 8 | | Sanitizable | 4832 | 18.2 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | | 360 | 33.4 | 800 | 55.16 | 122 | 48.6 |
| DairyUF 10K 3838-30 | | Sanitizable | 1805 | 6.8 | 38 | 96.5 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | | 80 | 7.4 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 10K 3838-46 | | Sanitizable | 1805 | 6.8 | 38 | 96.5 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | | 60 | 5.6 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 10K 4336-30 | | Sanitizable | 2097 | 7.9 | 35.5 | 90.2 | 4.28 | 10.87 | 0.83 | 2.1 | | | | | 0.0 | | 90 | 8.3 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 10K 4336-46 | | Sanitizable | 2097 | 7.9 | 35.5 | 90.2 | 4.28 | 10.87 | 0.83 | 2.1 | | | | | 0.0 | | 70 | 6.5 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 10K 4338-30 | | Sanitizable | 2097 | 7.9 | 38 | 96.5 | 4.28 | 10.87 | 0.83 | 2.1 | | | | | 0.0 | | 80 | 7.4 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 10K 6338-30 | | Sanitizable | 4195 | 15.8 | 38 | 96.5 | 6.36 | 10.87 | 1.138 | 2.9 | | | | | 0.0 | | 200 | 18.5 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 10K 6338-46 | | Sanitizable | 4195 | 15.8 | 38 | 96.5 | 6.36 | 16.15 | 1.138 | 2.9 | | | | | 0.0 | | 150 | 13.9 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 10K 6338-65 | | Sanitizable | 4195 | 15.8 | 38 | 96.5 | 6.36 | 16.15 | 1.138 | 2.9 | | | | | 0.0 | | 120 | 11.1 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 10K 6338-80 | | Sanitizable | 4195 | 15.8 | 38 | 96.5 | 6.36 | 16.15 | 1.138 | 2.9 | | | | | 0.0 | | 100 | 9.3 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 10K 8038-30 | | Sanitizable | 4832 | 18.2 | 38 | 96.5 | 7.9 | 16.15 | 1.125 | 2.9 | | | | | 0.0 | | 360 | 33.4 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 10K 8038-46 | | Sanitizable | 4832 | 18.2 | 38 | 96.5 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | | 280 | 26.0 | 150 | 10.34 | 131 | 52.2 |
| DairyUF 10K 8038-65 | | Sanitizable | 4832 | 18.2 | 38 | 96.5 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | | 215 | 19.9 | 150 | 10.34 | 131 | 52.2 |
| SWC-2514 | | Seawater | 110 | 0.4 | 14 | 35.6 | 2.4 | 6.10 | 0.75 | 1.9 | 99.4 | 99.0 | | | 1.0 | 0.45 | 5 | 0.5 | 1000 | 68.95 | 113 | 45.0 |
| SWC-2521 | | Seawater | 220 | 0.8 | 21 | 53.3 | 2.4 | 6.10 | 0.75 | 1.9 | 99.4 | 99.0 | | | 2.0 | 0.9 | 10 | 0.9 | 1000 | 68.95 | 113 | 45.0 |
| SWC-2540 | | Seawater | 520 | 2.0 | 40 | 101.6 | 2.4 | 6.10 | 0.75 | 1.9 | 99.4 | 99.0 | | | 4.0 | 1.8 | 26 | 2.4 | 1000 | 68.95 | 113 | 45.0 |
| SWC-4014 | | Seawater | 370 | 1.4 | 14 | 35.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.4 | 99.0 | | | 3.1 | 1.4 | 17 | 1.6 | 1000 | 68.95 | 113 | 45.0 |
| SWC-4021 | | Seawater | 640 | 2.4 | 21 | 53.3 | 3.95 | 10.03 | 0.75 | 1.9 | 99.4 | 99.0 | | | 4.0 | 1.8 | 29 | 2.7 | 1000 | 68.95 | 113 | 45.0 |
| SWC1-4040 | | Seawater | 1200 | 4.5 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.5 | 99.5 | | | 7.9 | 3.6 | 85 | 7.9 | 1000 | 68.95 | 113 | 45.0 |
| SWC1-8040 | | Seawater | 5000 | 18.8 | 40 | 101.6 | 7.95 | 20.19 | 1.50 | 3.8 | 99.5 | 99.5 | | | 36.2 | 16.4 | | | | | | |
| SWC2-4040 | | Seawater | 1500 | 5.7 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.0 | 99.0 | | | 7.9 | 3.6 | 70 | 6.5 | 1000 | 68.95 | 113 | 45.0 |
| SWC2-8040 | | Seawater | 6200 | 23.4 | 40 | 101.6 | 7.95 | 20.19 | 1.50 | 3.8 | 99.0 | 99.0 | | | 36.2 | 16.4 | | | | | | |
| SWC3-8040 | | Seawater | 5900 | 22.2 | 40 | 101.6 | 7.95 | 20.19 | 1.50 | 3.8 | 99.6 | 99.5 | | | 36.2 | 16.4 | | | | | | |
| SWC4+8040 | | Seawater | 6500 | 24.5 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.8 | 99.7 | | | 36.2 | 16.4 | 400 | 37.1 | 1200 | 82.74 | 113 | 45.0 |
| SWC4B | | Seawater | 6500 | 24.5 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.8 | 99.7 | | | 36.2 | 16.4 | 400 | 37.1 | 1200 | 82.74 | 113 | 45.0 |
| SWC4B-MAX | | Seawater | 7200 | 27.1 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.8 | 99.7 | | | 36.2 | 16.4 | 440 | 40.8 | 1200 | 82.74 | 113 | 45.0 |
| SWC4-LD | | Seawater | 6500 | 24.5 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.8 | 99.7 | | | 36.2 | 16.4 | 400 | 37.1 | 1200 | 82.74 | 113 | 45.0 |
| SWC4-MAX | | Seawater | 7200 | 27.1 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.8 | 99.7 | | | 36.2 | 16.4 | 440 | 40.8 | 1200 | 82.74 | 113 | 45.0 |
| SWCB-8040 | | Seawater | 6500 | 24.5 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.8 | 99.7 | | | 36.2 | 16.4 | 400 | 37.1 | 1200 | 82.74 | 113 | 45.0 |
| SWCB-MAX-8040 | | Seawater | 1900 | 7.2 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.7 | 99.5 | | | 7.9 | 3.6 | 440 | 40.8 | 1200 | 82.74 | 113 | 45.0 |
| SWC5-4040 | | Seawater | 1900 | 7.2 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.7 | 99.5 | | | 7.9 | 3.6 | 85 | 7.9 | 1200 | 82.74 | 113 | 45.0 |
| SWC5-LD | | Seawater | 9000 | 33.9 | 40 | 101.6 | 7.89 | 20.04 | 1.13 | 2.9 | 99.8 | 99.7 | | | 36.2 | 16.4 | 400 | 37.1 | 1200 | 82.74 | 113 | 45.0 |
| SWC5-LD-4040 | | Seawater | 1750 | 6.6 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.7 | 99.5 | | | 7.9 | 3.6 | 80 | 7.4 | 1200 | 82.74 | 113 | 45.0 |
| SWC5-MAX | | Seawater | 9900 | 37.3 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.8 | 99.7 | | | 36.2 | 16.4 | 440 | 40.8 | 1200 | 82.74 | 113 | 45.0 |
| SWC6-4040 | | Seawater | 2500 | 9.4 | 40 | 101.6 | 3.95 | 10.03 | 0.75 | 1.9 | 99.7 | 99.5 | | | 7.9 | 3.6 | 85 | 7.9 | 1000 | 68.95 | 113 | 45.0 |
| SWC6-8040 | | Seawater | 12000 | 45.2 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.8 | 99.7 | | | 36.2 | 16.4 | 400 | 37.1 | 1200 | 82.74 | 113 | 45.0 |
| SWC6-MAX | | Seawater | 13200 | 49.7 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.8 | 99.7 | | | 36.2 | 16.4 | 440 | 40.8 | 1200 | 82.74 | 113 | 45.0 |
| SWC6-LD | | Seawater | 12000 | 45.2 | 40 | 101.6 | 7.89 | 20.04 | 1.125 | 2.9 | 99.8 | 99.7 | | | 36.2 | 16.4 | 400 | 37.1 | 1200 | 82.74 | 113 | 45.0 |
| HYDRACoRe10-3838-30 | | Process | 1832 | 6.9 | 38 | 96.5 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | | 80 | 7.4 | 600 | 41.37 | 140 | 55.8 |
| HYDRACoRe10-3838-46 | | Process | 1832 | 6.9 | 38 | 96.5 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | | 60 | 5.6 | 600 | 41.37 | 140 | 55.8 |
| HYDRACoRe10-3838-65 | | Process | 1832 | 6.9 | 38 | 96.5 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | | 50 | 4.6 | 600 | 41.37 | 140 | 55.8 |
| HYDRACoRe10-8038-30 | | Process | 4832 | 18.2 | 38 | 96.5 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | | 360 | 33.4 | 600 | 41.37 | 140 | 55.8 |
| HYDRACoRe10-8038-46 | | Process | 4832 | 18.2 | 38 | 96.5 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | | 280 | 26.0 | 600 | 41.37 | 140 | 55.8 |
| HYDRACoRe10-8038-65 | | Process | 4832 | 18.2 | 38 | 96.5 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | | 215 | 19.9 | 600 | 41.37 | 140 | 55.8 |
| HYDRACoRe10-8040-30 | | Process | 6027 | 22.7 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | | 360 | 33.4 | 600 | | | |

| Part Number | Model Name / Description | Type | Flow | | Length (A) | | OUTPUT O.D. (B) | | FEED O.D. (C) | | Average NaCl rejection | Minimum NaCl rejection | Average MgSO4I rejection | Minimum MgSO4 rejection | Shipping Weight | | Membrane Active Area | | Max. Pressure | | Max. Temperature | |
|-------------|--|-----------------|-------|----------------------|------------|-------|-----------------|--------|---------------|-------|------------------------|------------------------|--------------------------|-------------------------|-----------------|-------|----------------------|-------|-----------------|----------------|------------------|------|
| | | | gpd | m ³ / day | inch | cm | inch | cm | inch | cm | inch | cm | % | % | % | % | lbs | kg | ft ² | m ² | psi | KPa |
| | HYDRACoRe50-3838-46 | Process | 1832 | 6.9 | 38 | 96.5 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | 60 | 5.6 | 600 | 41.37 | 140 | 55.8 | |
| | HYDRACoRe50-3838-65 | Process | 1832 | 6.9 | 38 | 96.5 | 3.78 | 9.60 | 0.83 | 2.1 | | | | | 0.0 | 50 | 4.6 | 600 | 41.37 | 140 | 55.8 | |
| | HYDRACoRe50-8038-30 | Process | 4832 | 18.2 | 38 | 96.5 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | 360 | 33.4 | 600 | 41.37 | 140 | 55.8 | |
| | HYDRACoRe50-8038-46 | Process | 4832 | 18.2 | 38 | 96.5 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | 280 | 26.0 | 600 | 41.37 | 140 | 55.8 | |
| | HYDRACoRe50-8038-65 | Process | 4832 | 18.2 | 38 | 96.5 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | 215 | 19.9 | 600 | 41.37 | 140 | 55.8 | |
| | HYDRACoRe50-8040-30 | Process | 6027 | 22.7 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | 360 | 33.4 | 600 | 41.37 | 140 | 55.8 | |
| | HYDRACoRe50-8040-46 | Process | 4832 | 18.2 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | 280 | 26.0 | 600 | 41.37 | 140 | 55.8 | |
| | HYDRACoRe50-8040-65 | Process | 4832 | 18.2 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | 215 | 19.9 | 600 | 41.37 | 140 | 55.8 | |
| | HYDRACoRe70pHT-4040-46 | Process | 1805 | 6.8 | 40 | 101.6 | 3.98 | 10.11 | 0.75 | 1.9 | | | | | 0.0 | 70 | 6.5 | 600 | 41.37 | 158 | 62.9 | |
| | HYDRACoRe70pHT-8038-46 | Process | 1805 | 6.8 | 40 | 101.6 | 7.9 | 20.07 | 1.125 | 2.9 | | | | | 0.0 | 275 | 25.5 | 600 | 41.37 | 158 | 62.9 | |
| | SuPRO 8338-60 | Process | 1805 | 6.8 | 38 | 96.5 | 8.35 | 21.21 | 1.138 | 2.9 | | | | | 0.0 | 222 | 20.6 | 200 | 13.79 | 158 | 62.9 | |
| | SuPRO 8338-80 | Process | 1805 | 6.8 | 38 | 96.5 | 8.35 | 21.21 | 1.138 | 2.9 | | | | | 0.0 | 184 | 17.1 | 200 | 13.79 | 158 | 62.9 | |
| | SuPRO 8338-100 | Process | 1805 | 6.8 | 38 | 96.5 | 8.35 | 21.21 | 1.138 | 2.9 | | | | | 0.0 | 155 | 14.4 | 200 | 13.79 | 158 | 62.9 | |
| | HYDRAcap-40 | UltraFiltration | 27000 | 101.7 | 47 1/4 | 120.0 | 2.00 | 5.08 | 2.00 | 5.08 | | | | | 61.7 | 28.0 | 320 | 29.7 | 73 | 5.03 | 104 | 41.4 |
| | HYDRAcap40-LD | UltraFiltration | 27000 | 101.7 | 43 | 109.2 | 46.125 | 117.16 | 47.25 | 120.0 | | | | | 61.7 | 28.0 | 320 | 29.7 | 73 | 5.03 | 104 | 41.4 |
| | HYDRAcap MAX-40 | UltraFiltration | 34800 | 131.1 | 53.74 | 136.5 | 2.00 | 5.08 | 2.00 | 5.08 | | | | | 161.0 | 73.0 | 560 | 51.9 | 73 | 5.03 | 104 | 41.4 |
| | HYDRAcap-60 | UltraFiltration | 42400 | 159.8 | 67.25 | 170.8 | 2.00 | 5.08 | 2.00 | 5.08 | | | | | 97.0 | 44.0 | 500 | 46.4 | 73 | 5.03 | 104 | 41.4 |
| | HYDRAcap60-LD | UltraFiltration | 27000 | 101.7 | 67.25 | 170.8 | 2.00 | 5.08 | 2.00 | 5.08 | | | | | 97.0 | 44.0 | 323 | 30.0 | 73 | 5.03 | 104 | 41.4 |
| | HYDRAcap MAX-60 | UltraFiltration | 54500 | 205.4 | 72.15 | 183.3 | 2.00 | 5.08 | 2.00 | 5.08 | | | | | 220.5 | 100.0 | 840 | 77.9 | 73 | 5.03 | 104 | 41.4 |
| | HYDRAcap-80 | UltraFiltration | 57000 | 214.8 | 87.25 | 221.6 | 2.00 | 5.08 | 2.00 | 5.08 | | | | | 119.1 | 54.0 | 670 | 62.1 | 73 | 5.03 | 104 | 41.4 |
| | HYDRAcap-MAX-80 | UltraFiltration | 73500 | 277.0 | 92.15 | 234.1 | 83.11 | 211.10 | 87.90 | 223.3 | | | | | 260.2 | 118.0 | 1130 | 104.8 | 73 | 5.03 | 104 | 41.4 |