

## NOCCHI ADRY

### THREE PHASE ELECTRICAL PANELS FOR CONTROL OF ONE OR MORE ELECTRIC DRAINAGE AND WASTE WATER PUMPS WITH STAR/DELTA STARTING

#### MAIN COMPONENTS

- IP 54 plastic enclosure
- Main switch
- Fuse holder with fuses for electric pump
- Fuse holder with fuses for auxiliary circuit
- Contactor with thermal relay
- Transformer for auxiliary circuit
- Terminal board for level control devices
- Cable clamp
- Electronic signaling and control board (Volt/Amp)
- Thermal cutout trip led
- Pump running indicator led
- Line ON indicator led

#### TECHNICAL SPECIFICATIONS

- Protection rating: IP54
- Power supply voltage: 400V 3F 50 Hz
- External dimensions 500 - 750 - 250 mm

#### OPERATION

- Manual via MAN/AUT selector
- Automatic via float switch

#### APPLICATION LIMITS

- Ambient temperature: -5 / +40 °C
- Relative humidity: 50% at 40°C condensate free.
- Reference standards: EN 60730 - EN 60439

#### ADRY 20

- Electronic signaling and control board with sequential start-up inverter
- Electrical panel for control of two electric pumps
- Weight: Kg 15 - 85

#### ADRY 10

- Electronic control board
- Electrical panel for control of one pump
- Weight: 12 - 60 kg

#### OPTIONAL ACCESSORIES

- UZA00200 Visual and acoustic alarm
- CE040030 fins for wall mounting
- Floats (see relative table)

MODEL	Volt	Power		Field of application A		Compatible el. pumps
		kW	Hp	min	max	
E.P. ADRY10/900	400 3F	9	12	12.9	19	Sewage pumps
E.P. ADRY10/1100	400 3F	11	15	17.2	24.1	
E.P. ADRY10/1500	400 3F	15	20	22.4	32.8	
E.P. ADRY10/2200	400 3F	22	30	29.3	44.8	
E.P. ADRY10/2500	400 3F	25	33.5	37.9	55.2	
E.P. ADRY20/900	400 3F	2x9	2x12	12.9	19	
E.P. ADRY20/1100	400 3F	2x11	2x15	17.2	24.1	
E.P. ADRY20/1500	400 3F	2x15	2x20	22.4	32.8	
E.P. ADRY20/2200	400 3F	2x22	2x30	29.3	44.8	
E.P. ADRY20/2500	400 3F	2x25	2x33.5	37.9	55.2	

