

High Purity Filtration With Low Cost Melt Blown Depth Cartridges

Parker's Fulflo® EcoBond Cartridges are the most economical high purity filter cartridges available. Featuring a graded density matrix of uniform polypropylene fibers, the EcoBond provides consistent filtration for a wide variety of fluids. No fiber finish or surfactants are present to generate extractables leading to foaming or other undesirable effects on the filtrate.

Fulflo EcoBond Cartridges are available in nominal ratings of 1µm, 5µm, 10µm, 25 µm and 50µm.

Applications

- Photographic Chemicals
- DI Water
- Plating Solutions
- R.O. Prefiltration
- Organic Solvents
- Oilfield Fluids
- Food & Beverages
- Membrane Prefiltration
- Chemical Processing Fluids
- Potable Water
- Bleach



Features and Benefits

- Fixed pore structure provides efficiency integrity and optimum particle retention.
- Thermally bonded melt blown fiber matrix provides dimensionally stable construction.
- Continuous fiber matrix prevents media migration and ensures consistent quality filtration performance.
- Finish-free construction provides optimum fluid purity and eliminates foaming condition.
- Superior inter-layer bonding eliminates contaminant unloading and channeling.
- Narrow range fiber size optimizes consistency of filtration performance.
- Polypropylene construction provides broad chemical compatibility for a variety of applications.
- All materials of construction are FDA listed as acceptable for potable and edible liquid contact according to CFR Title 21.
- Single component construction simplifies compatibility options and provides easy disposal.

Process Filtration Division



Melt Blown Depth Series

Specifications

Nominal Filtration Ratings:

- 1µm, 5µm, 10µm, 25µm, and 50µm.

Materials of Construction:

- Filter Medium: 100% melt blown polypropylene
- End Caps/Adapters (optional): polyolefin copolymer
- Seal Options: Various; refer to Ordering Information

Recommended Operating Conditions:

- Maximum Temperature:
 - @ 40 psid (2.7 bar): 80°F (27°C)
 - @ 20 psid (0.8 bar): 140°F (60°C)
- Maximum Recommended Flow Rate: 5 gpm per 10 in length
- Change Out ΔP: 30 psi (2.1 bar)
- Maximum Operating Differential Pressure @ Ambient Temperature: 40 psi (2.7 bar)

Dimensions:

- 1-1/16 in ID x 2-7/16 in OD (max)
- 10, 20, 30 and 40 in continuous nominal lengths

EBC Length Factors

Length (in)	Length Factor
9.75	1.0
10.00	1.0
19.50	2.0
20.00	2.0
29.25	3.0
30.00	3.0
39.00	4.0
40.00	4.0

EBC Flow Factors

Rating (µm)	Aqueous Service PSI/ GPM per 10 in Cartridge
EBC1	0.10
EBC5	0.08
EBC10	0.07
EBC25	0.06
EBC50	0.05

Flow Rate and Pressure Drop Formulas:

$$\text{Flow Rate (gpm)} = \frac{\text{Clean } \Delta P \times \text{Length Factor}}{\text{Viscosity} \times \text{Flow Factor}}$$

$$\text{Clean } \Delta P = \frac{\text{Flow Rate} \times \text{Viscosity} \times \text{Flow Factor}}{\text{Length Factor}}$$

Notes:

- Clean ΔP is PSI differential at start.
- Viscosity is centistokes. Use Conversion Tables for other units.
- Flow Factor is ΔP/GPM at 1 cks for 10 in (or single).
- Length Factors convert flow or ΔP from 10 in (single length) to required cartridge length.

Ordering Information

EBC	10	M	10	—	TC	—	N																											
<i>Cartridge Code</i>	<i>Micrometer Rating (µm)</i>	<i>Filter Medium</i>	<i>Nominal Length</i>		<i>End Cap Options</i>		<i>Seal Options</i>																											
EcoBond Cartridge	1 5 10 25 50	M = FDA Polypropylene	<table border="0"> <thead> <tr> <th>Code</th> <th>in</th> <th>mm</th> </tr> </thead> <tbody> <tr><td>9-4</td><td>9-3/4</td><td>248</td></tr> <tr><td>10</td><td>10</td><td>254</td></tr> <tr><td>19-4</td><td>19-1/2</td><td>496</td></tr> <tr><td>20</td><td>20</td><td>508</td></tr> <tr><td>29-4</td><td>29-1/4</td><td>743</td></tr> <tr><td>30</td><td>30</td><td>762</td></tr> <tr><td>39-4</td><td>39</td><td>992</td></tr> <tr><td>40</td><td>40</td><td>1016</td></tr> </tbody> </table>	Code	in	mm	9-4	9-3/4	248	10	10	254	19-4	19-1/2	496	20	20	508	29-4	29-1/4	743	30	30	762	39-4	39	992	40	40	1016		None = DOE AR = 020 O-Ring/Recessed LL = 120 O-Ring (Both Ends) LR = 120 O-Ring/Recessed PR = 213 O-Ring/Recessed SC = 226 O-Ring/Closed SF = 226 O-Ring/Fin TC = 222 O-Ring/Closed TF = 222 O-ring/Fin XA = DOE w/Ext Core		None = No Gasket (DOE Only) N = Buna E = EPR S = Silicone V = Viton* T = Teflon Encapsulated Viton*
Code	in	mm																																
9-4	9-3/4	248																																
10	10	254																																
19-4	19-1/2	496																																
20	20	508																																
29-4	29-1/4	743																																
30	30	762																																
39-4	39	992																																
40	40	1016																																

* A trademark of E. I. du Pont de Nemours & Co.

Process Filtration Division

LENNTECH

info@lennotech.com

www.lennotech.com

Tel. +31-15-261.09.00

Fax. +31-15-261.62.89

