

LENNTECH

info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

INDUSTRIAL BIG BLUE/BIG CLEAR CARTRIDGE HOUSINGS



Big Blue and Big Clear Filter Housings offer the versatility to meet larger capacity filtration needs. This reduces the number of housings required for high-flow applications.

FEATURES/BENEFITS

Large capacity housing

Sumps constructed of durable reinforced polypropylene

Big Clear Filter Housings offer on-site examination of flow, performance and cartridge life

1.25" internal port to allow a greater volume of liquid to pass through the high-flow polypropylene cap more rapidly Accepts 4.5" diameter cartridges

Compatible with a broad range of chemicals

APPLICATIONS

Heavy sediment applications High-flow applications

OPTIONS

10" and 20" lengths available in opaque and clear

Cap available with 0.75", 1" or 1.5" NPT inlet and outlet ports

Blue polypropylene caps available with optional pressure relief/bleed button on inlet side of cap

NSF certified Big Blue configurations available

HOUSING SPECIFICATIONS

| | Big Blue | Big Clear | |
|---------|---------------|---------------|--|
| Housing | Polypropylene | Lexan | |
| Сар | Polypropylene | Polypropylene | |

Button Assembly 300 Series Stainless Steel, 300 Series Stainless Steel, EPDM, and Polypropylene EPDM, and Polypropylene

O-ring Buna-N Buna-N

Max. Temperature 100°F 100°F (37.8°C) (37.8°C)

Max. Pressure #10 Big Blue - 100 psi (6.9 bar) #10 Big Clear - 100 psi (6.9 bar)


#20 Big Blue - 90 psi (6.2 bar) #20: 90 psi (6.2 bar)

CAUTION: Protect against freezing to prevent cracking of the filter and water leakage.

| MODEL | INLET/OUTLET SIZE (IN.) | MAXIMUM DIMENSIONS | INITIAL ΔP (PSI) @ FLOW RATE (GPM) |
|---------------|-------------------------|----------------------------------|-------------------------------------|
| #10 Big Blue | .75 | 12.75" x 7.38" (324 mm x 187 mm) | 2 PSI @ 15 gpm (0.14 bar @ 57 Lpm) |
| #10 Big Blue | 1 | 13.30" x 7.45" (338 mm x 189 mm) | 1 PSI @ 15 gpm (0. 07 bar @ 57 Lpm) |
| #10 Big Blue | 1.5 | 13.45" x 7.45" (342 mm x 189 mm) | 1 PSI @ 20 gpm (0. 07 bar @ 76 Lpm) |
| #20 Big Blue | .75 | 23.04" x 7.38" (585 mm x 187 mm) | 2 PSI @ 15 gpm (0.14 bar @ 57 Lpm) |
| #20 Big Blue | 1 | 23.22" x 7.45" (590 mm x 189 mm) | 1 PSI @ 15 gpm (0.07 bar @ 57 Lpm) |
| #20 Big Blue | 1.5 | 23.74" x 7.45" (603 mm x 189 mm) | 1 PSI @ 20 gpm (0. 07 bar @ 76 Lpm) |
| #10 Big Clear | 1 | 13.30" x 7.28" (388 mm x 185 mm) | 1 PSI @ 15 gpm (0. 07 bar @ 57 Lpm) |
| #20 Big Clear | 1 | 23.22" x 7.28" (590mm x 185mm) | 1 PSI @ 15 gpm (0. 07 bar @ 57 Lpm) |

^{*} Not performance tested or certified by NSF.

PRESSURE DROP VS FLOW RATE



Flow Rate - gpm (Lpm)



FILTRATION & PROCESS



info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.