



TECHNICAL SHEET

PENTAIR

RO-2500 REVERSE OSMOSIS
DRINKING WATER SYSTEM



LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289



PENTAIR RO-2500* REVERSE OSMOSIS DRINKING WATER SYSTEM

TECHNICAL CHARACTERISTICS



- The finest level of water filtration available – filtering particles as small as 1/1000 of a micron
- Reduces bad taste & odor, chlorine taste & odor, sediment, arsenic III, arsenic V**
- Designed for use on chlorinated or non-chlorinated water supplies
- Comes complete with cartridges, a long-reach faucet, and installation hardware
- Great-tasting water for drinking and cooking
- Significantly less expensive than bottled water, with a reduced impact on the environment
- Produces clear, hard ice

APPLICATIONS

- Residential point-of-use drinking water
- Undersink installation
- Pretreatment for icemakers

SPECIFICATIONS

Maximum dimensions:

System	394 x 356 x 133 mm 15½ (W) x 14 (H) D x 5¼ (D) inches
Tank	343 x 229 x 203 mm 13½ (W) x 9 (H) D x 8 (D) inches
Pressure range	2.07-8.6 bar (30-125 psi)
Filter life	6-12 months***
Membrane performance	132.5 L per day (35 gpd)

* Not performance tested or certified by NSF

** Based on manufacturer's internal testing

*** Dependent on daily water consumption

Contact us:

LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289