Poly Glass™ Vessels

The ideal pressure vessel for residential and light commercial water softener / filtration applications.

Structural Poly Glass™ pressure vessels provide years of reliable service for water softener and water filtration applications.

These slim-diameter tanks hold up to 49 gallons of water and offer unmatched strength and chemical resistance. All 6"-13" Poly Glass vessels are backed by an exclusive 10-year warranty. All 14"-16"

Poly Glass vessels are backed by an exclusive 5-year warranty.



Material of construction

Inner shell material: Polyethylene

Available inlets: See chart

Operating parameters

Maximum operating pressure: 150 psi

Maximum operating temperature: 120° F

Design parameters - Pentair

Safety factor: 4:1 (Minimum burst at 600 psi)

Cycle test: 250,000 cycles without leakage

Design parameters

Safety factor: 4:1 (Minimum burst at 600 psi)

Cycle test: 100,000 cycles without leakage



info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289



Poly Glass Specifications

| | C! | Contant | Halaktard Davis | Heliahteeda Basa | O a sa a libra | 0.44- | | B. Oliveiro |
|----------|------------------|------------------------|-------------------------------|--------------------------------|------------------------------|---------------|------------|---------------------------|
| Part No. | Size (Inches) | System Connection | Height w/ Base Inches / mm | Height w/o Base Inches / mm | Capacity Gallons / Liters | Cubic Feet | Colors | Minimum Order Quantity |
| 30109 | 06 x 13 | 2.5" Threaded | 13.2 / 335 | 12.6 / 320 | 1.1 / 4.2 | 0.15 | AL, BL, NA | See Factory |
| 30127 | 06 x 18 | 2.5" Threaded | 18.6 / 472 | 18.0 / 457 | 1.8 / 6.8 | 0.24 | All | None |
| 30151 | 06 x 35 | 2.5" Threaded | 35.8 / 909 | 35.2 / 894 | 3.8 / 14.4 | 0.51 | All | None |
| 30190 | 07 x 35 | 2.5" Threaded | 35.6 / 904 | 35.3 / 897 | 5.2 / 19.7 | 0.7 | AL, BL, NA | See Factory |
| 30213 | 07 x 44 | 2.5" Threaded | 43.7 / 1110 | 43.4 / 1102 | 6.7 / 25.4 | 0.9 | AL, BL, NA | See Factory |
| 31835 | 08 x 18 | 2.5" Threaded | 18.8 / 478 | 18.5 / 470 | 3.28 / 12.0 | - | AL, NA | See Factory |
| 30264 | 08 x 35 | 2.5" Threaded | 35.6 / 904 | 35.3 / 897 | 6.6 / 25.0 | 0.88 | All | None |
| 30286 | 08 x 40 | 2.5" Threaded | 40.2 / 1021 | 39.9 / 1013 | 7.8 / 29.5 | 1.04 | All | None |
| 30305 | 08 x 44 | 2.5" Threaded | 44.4 / 1128 | 44.1 / 1120 | 8.7 / 32.9 | 1.16 | All | None |
| 30317 | 09 x 18 | 2.5" Threaded | 18.6 / 472 | 18.0 / 457 | 3.9 / 14.8 | 0.52 | AL, BL, NA | See Factory |
| 30347 | 09 x 35 | 2.5" Threaded | 35.6 / 904 | 35.3 / 897 | 8.3 / 31.4 | 1.11 | All | None |
| 30360 | 09 x 40 | 2.5" Threaded | 40.2 / 1021 | 39.9 / 1013 | 9.5 / 31.4 | 1.27 | All | None |
| 30383 | 09 x 48 | 2.5" Threaded | 48.2 / 1224 | 47.9 / 1217 | 11.8 / 44.7 | 1.58 | All | None |
| 30460 | 10 x 35 | 2.5" Threaded | 35.6 / 904 | 35.3 / 897 | 10.2 / 38.6 | 1.36 | All | None |
| 30491 | 10 x 40 | 2.5" Threaded | 40.3 / 1024 | 40.1 / 1018 | 11.5 / 43.5 | 1.54 | All | None |
| 30523 | 10 x 44 | 2.5" Threaded | 44.6 / 1133 | 44.4 / 1128 | 13.1 / 49.6 | 1.75 | All | None |
| 30546 | 10 x 47 | 2.5" Threaded | 47.4 / 1204 | 46.9 / 1191 | 15.1 / 57.0 | 2.02 | All | None |
| 30579 | 10 x 54 | 2.5" Threaded | 54.8 / 1392 | 54.6 / 1387 | 16.4 / 62.0 | 2.19 | All | None |
| 32065 | 10 x 54 | 2.5" Threaded 1.25 TDH | 54.8 / 1392 | 54.6 / 1387 | 16.4 / 62.0 | 2.19 | All | None |
| 30615 | 12 x 42 | 2.5" Threaded | 42.8 / 1087 | 42.2 / 1072 | 19.1 / 72.0 | 2.55 | AL, NA | See Factory |
| 30617 | 12 x 42 | 4.5" Threaded (BTRS) | 42.8 / 1087 | 42.2 / 1072 | 19.1 / 72.0 | 2.55 | AL, NA | See Factory |
| 30646 | 12 x 48 | 2.5" Threaded | 48.8 / 1240 | 48.4 / 1229 | 20.6 / 78.0 | 2.75 | All | None |
| 30666 | 12 x 52 | 2.5" Threaded | 52.9 / 1344 | 52.4 / 1331 | 22.2 / 84.0 | 2.97 | All | None |
| 30669 | 12 x 52 | 4.0" Threaded | 52.9 / 1344 | 52.4 / 1331 | 22.2 / 84.0 | 2.97 | AL, BL, NA | See Factory |
| 32127 | 12 x 52 | 4.5" Threaded (BTRS) | 52.9 / 1344 | 52.4 / 1331 | 22.2 / 84.0 | 2.97 | AL, NA | See Factory |
| 30721 | 13 x 54 | 2.5" Threaded | 54.6 / 1387 | 53.9 / 1369 | 27.5 / 104.0 | 3.68 | All | None |
| 30724 | 13 x 54 | 4.0" Threaded | 54.6 / 1387 | 53.9 / 1369 | 27.5 / 104.0 | 3.68 | AL, BL, NA | See Factory |
| 31389 | 14 x 47 | 2.5" Threaded | 46.5 / 1181 | 46.0 / 1168 | 27.5 / 104.0 | 3.68 | AL, NA | See Factory |
| 30745 | 14 x 47 | 4.0" Threaded | 46.5 / 1181 | 46.0 / 1168 | 27.5 / 104.0 | 3.68 | AL, NA | See Factory |
| 32006 | 14 x 47 | 4.5" Threaded (BTRS) | 46.5 / 1181 | 46.0 / 1168 | 27.5 / 104.0 | 3.68 | AL, NA | See Factory |
| 30783 | 14 x 65 | 2.5" Threaded | 64.6 / 1641 | 64.3 / 1633 | 40.6 / 154.0 | 5.43 | AL, BL, NA | See Factory |
| 30785 | 14 x 65 | 4.0" Threaded | 64.6 / 1641 | 64.3 / 1633 | 40.6 / 154.0 | 5.43 | All | None |
| 31627 | 16 x 65 | 2.5" Threaded | 64.6 / 1641 | 64.3 / 1633 | 49.0 / 185.0 | 6.55 | AL, BL, NA | See Factory |
| 30912 | 16 x 65 | 4.0" Threaded | 64.6 / 1641 | 64.3 / 1633 | 49.0 / 185.0 | 6.55 | All | None |

Color Options: AL - Almond BL - Blue BK - Black GR - Gray NA - Natural