

PRODUCT DATA SHEET

Purofine® PFA500SPlus

Polystyrenic Macroporous, Type I
Strong Base Anion Resin, Chloride
form, Uniform Particle Size, Sugar
Grade

PRINCIPAL APPLICATIONS

- Demineralization - Sugar solutions
- Silica Removal

ADVANTAGES

- Efficient regeneration
- Uniform particle size
- Good resistance to organic fouling
- Enhanced resistance to thermal and osmotic shock
- High operating capacity

TYPICAL PACKAGING

- 1 ft³ Sack
- 25 L Sack
- 5 ft³ Drum (Fiber)
- 1 m³ Supersack
- 42 ft³ Supersack

LENNTECH
WATER TREATMENT Solutions

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Macroporous polystyrene crosslinked with divinylbenzene
Appearance	Spherical Beads
Functional Group	Type I Quaternary Ammonium
Ionic Form	Cl ⁻ form
Total Capacity	1.15 eq/L (25.1 Kgr/ft ³) (Cl ⁻ form)
Moisture Retention	57 - 63 % (Cl ⁻ form)
Mean Diameter	570 ± 50 µm
Uniformity Coefficient (max.)	1.2
Reversible Swelling, Cl ⁻ → OH ⁻ (max.)	15 %
Specific Gravity	1.08
Shipping Weight (approx.)	670 - 690 g/L (41.9 - 43.1 lb/ft ³)
Temperature Limit	100 °C (212.0 °F) (Cl ⁻ form)
Temperature Limit	65 °C (149.0 °F) (OH ⁻ form)



LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289