

PRODUCT DATA SHEET

Purofine® PFC100x10H

Polystyrenic Gel, Strong Acid Cation
Resin, Hydrogen form, Uniform
Particle Size

PRINCIPAL APPLICATIONS

- Demineralization - Industrial

ADVANTAGES

- Efficient regeneration
- Efficient separation
- Excellent physical and chemical stability
- High operating capacity
- Lower pressure drop versus standard resin

SYSTEMS

- Coflow regenerated systems
- Counterflow regenerated systems

TYPICAL PACKAGING

- 1 ft³ Sack
- 25 L Sack
- 5 ft³ Drum (Fiber)
- 1 m³ Supersack
- 42 ft³ Supersack

LENNTECH
WATER TREATMENT Solutions

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Gel polystyrene crosslinked with divinylbenzene
Appearance	Spherical Beads
Functional Group	Sulfonic Acid
Ionic Form	H ⁺ form
Total Capacity	2.2 eq/L (48.1 Kgr/ft ³) (Na ⁺ form)
Moisture Retention	47 - 50 % (H ⁺ form)
Mean Diameter	570 ± 50 µm
Uniformity Coefficient	1.1 - 1.2
Reversible Swelling, Na ⁺ → H ⁺ (max.)	6 %
Specific Gravity	1.22
Shipping Weight (approx.)	755 - 780 g/L (47.2 - 48.8 lb/ft ³)
Temperature Limit	120 °C (248.0 °F)



LENNTECH
info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289