

## PRODUCT DATA SHEET

# Purolite® IP9

Polyvinylchloride, Inert Polymer,  
Underbed Applications

### PRINCIPAL APPLICATIONS

- Bottom layer in industrial water applications

### ADVANTAGES

- Heavier than water treatment resins
- Regeneration chemical resistant

**LENNTECH**  
*WATER TREATMENT SOLUTIONS*

### SYSTEMS

- Demineralization systems
- Dealkalization systems
- Softening systems

### TYPICAL PACKAGING

- 25 L Sack
- 5 ft<sup>3</sup> Drum (Fiber)
- 1 m<sup>3</sup> Supersack
- 42 ft<sup>3</sup> Supersack

### TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Polyvinylchloride
Appearance	Light Blue Lenses
Length	4.5 - 5.5 mm
Width	4.5 - 5.5 mm
Thickness	2.0 - 3.0 mm
Specific Gravity (min.)	1.3
Shipping Weight (approx.)	850 - 950 g/L (53.1 - 59.4 lb/ft <sup>3</sup> )
Temperature Limit	70 °C (158.0 °F)



**LENNTECH**

info@lennotech.com Tel. +31-152-610-900  
www.lennotech.com Fax. +31-152-616-289