

PRODUCT DATA SHEET

Purolite® NRW100x10

Polystyrenic Gel, Strong Acid Cation
Resin, Hydrogen form, Nuclear
Grade

PRINCIPAL APPLICATIONS

- Primary coolant polishing

TYPICAL PACKAGING

- 1 CF Box
- 5 ft³ Drum (Fiber)



TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Gel polystyrene crosslinked with divinylbenzene
Appearance	Spherical Beads
Functional Group	Sulfonic Acid
Ionic Form	H ⁺ form
Total Capacity	2 eq/L (43.7 Kgr/ft ³) (H ⁺ form)
Moisture Retention	46 - 50 % (H ⁺ form)
Particle Size Range	425 - 1200 µm
< 425 µm (max.)	2 %
Uniformity Coefficient (max.)	1.7
Conversion (min.)	99.9 % (H ⁺ form)
Impurities Iron (max.)	50 ppm
Impurities Sodium (max.)	40 ppm
Impurities Heavy Metals (max.)	40 ppm
Specific Gravity	1.22
Shipping Weight (approx.)	770 - 815 g/L (48.1 - 50.9 lb/ft ³)
Temperature Limit	120 °C (248.0 °F)



LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289