

PRODUCT DATA SHEET

Purolite® NRW160

Polystyrenic Macroporous, Strong
Acid Cation Resin, Hydrogen form,
Nuclear Grade

PRINCIPAL APPLICATIONS

- Cobalt Selective
- Cesium Selective
- Radioactive Isotope Removal

TYPICAL PACKAGING

- 1 CF Box
- 5 ft³ Drum (Fiber)

LENNTECH
WATER TREATMENT SOLUTIONS

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Macroporous polystyrene crosslinked with divinylbenzene
Appearance	Spherical Beads
Functional Group	Sulfonic Acid
Ionic Form	H ⁺ form
Total Capacity	2.1 eq/L (45.9 Kgr/ft ³) (H ⁺ form)
Moisture Retention	43 - 48 % (H ⁺ form)
Particle Size Range	425 - 1200 µm
< 425 µm (max.)	2 %
Uniformity Coefficient (max.)	1.7
Conversion (min.)	99.9 % (H ⁺ form)
Impurities Iron (max.)	50 ppm
Impurities Sodium (max.)	40 ppm
Impurities Heavy Metals (max.)	40 ppm
Specific Gravity	1.21
Shipping Weight (approx.)	760 - 800 g/L (47.5 - 50.0 lb/ft ³)
Temperature Limit	120 °C (248.0 °F)



LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289