

PRODUCT DATA SHEET

Purolite® NRW160Li7

Polystyrenic Macroporous, Strong
Acid Cation Resin, Lithium7 form,
Nuclear Grade

PRINCIPAL APPLICATIONS

- Decontamination - Radioactive circuits

SYSTEMS

- Radioactive Circuits

TYPICAL PACKAGING

- 1 CF Box
- 5 ft³ Drum (Fiber)

LENNTECH
WATER TREATMENT Solutions

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Macroporous polystyrene crosslinked with divinylbenzene
Appearance	Spherical Beads
Functional Group	Sulfonic Acid
Ionic Form	⁷ Li ⁺ form
Total Capacity	2.3 eq/L (50.3 Kgr/ft ³) (⁷ Li ⁺ form)
Moisture Retention	43 - 48 % (H ⁺ form)
Particle Size Range	425 - 1200 µm
< 425 µm (max.)	2 %
Uniformity Coefficient (max.)	1.7
Conversion (min.)	99.9 % (⁷ Li ⁺ form)
Impurities Iron (max.)	50 ppm
Impurities Sodium (max.)	40 ppm
Impurities Heavy Metals (max.)	40 ppm
Specific Gravity	1.24
Shipping Weight (approx.)	770 - 810 g/L (48.1 - 50.6 lb/ft ³)
Temperature Limit	120 °C (248.0 °F)



LENNTECH

info@lennotech.com Tel. +31-152-610-900

www.lennotech.com Fax. +31-152-616-289