

## PRODUCT DATA SHEET

# Shallow Shell™ SSTPPC8000E

Polystyrenic Gel, Strong Acid Cation  
Resin, Sodium form, Shallow Shell™  
Technology\*, Puropack Grade

**LENNTECH**  
WATER TREATMENT SOLUTIONS

## PRINCIPAL APPLICATIONS

- Demineralization - Potable Water
- Softening - Potable Water

## ADVANTAGES

- Highest regeneration efficiency
- Highest salt efficiency
- Excellent physical and chemical stability
- Low Rinse Volumes
- Excellent physical and chemical stability

## SYSTEMS

- Potable water treatment
- Packed Bed Systems
- Coflow regenerated systems

## REGULATORY APPROVALS

- Certified by the WQA to NSF/ANSI-61 Standard

## TYPICAL PACKAGING

- 1 ft³ Sack
- 5 ft³ Sack
- 5 ft³ Drum

\* SST® is a registered trademark of Purolite Corporation.

## TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Gel polystyrene crosslinked with divinylbenzene
Appearance	Spherical Beads
Functional Group	Sulfonic Acid
Ionic Form	Na <sup>+</sup>
Dry Weight Capacity (min.)	4.0 eq/kg (Na <sup>+</sup> form)
Moisture Retention	42 - 48 % (Na <sup>+</sup> form)
Mean Diameter	650 ± 50 µm
Uniformity Coefficient (max.)	1.25
Reversible Swelling, Na <sup>+</sup> → H <sup>+</sup> (max.)	6 %
Specific Gravity	1.2
Shipping Weight (approx.)	775 - 825 g/L (48.4 - 51.6 lb/ft³)
Temperature Limit	100 °C (212.0 °F)



**LENNTECH**

info@lennotech.com Tel. +31-152-610-900  
www.lennotech.com Fax. +31-152-616-289