

PRODUCT DATA SHEET

Purolite® CT269DR

Polystyrenic Macroporous, Strong
Acid Cation Resin, Hydrogen form,
Catalyst, Dry

PRINCIPAL APPLICATIONS

- TAME Production
- MTBE Production
- Catalysis

TYPICAL PACKAGING

- 5 ft³ Drum (Fiber)

LENNTECH
WATER TREATMENT SOLUTIONS

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Macroporous polystyrene crosslinked with divinylbenzene
Appearance	Spherical Beads
Functional Group	Sulfonic Acid
Ionic Form	H ⁺ form
Dry Weight Capacity (min.)	5.2 eq/kg
Moisture Retention	51 - 57 % (H ⁺ form)
Residual Moisture (max.)	3 %
Particle Size Range	425 - 1200 µm
< 425 µm (max.)	2 %
Uniformity Coefficient (max.)	1.7
Surface Area	35 - 50 m ² /g
Pore Volume	0.3 - 0.5 mL/g
Median Pore Diameter	250 - 425 Å
Specific Gravity	1.2
Temperature Limit	180 °C (356.0 °F)



LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289