



The Specialty Membrane Company

## PRODUCT SPECIFICATION

### TurboClean® UF Element For Beverage Applications

Model	Permeate Flow*	Nominal M.W.C.O.
TurboClean® Bev 8040-UF	14,000 GPD (53 m <sup>3</sup> /d)	10,000 Da.

\* Performance shown is based on the following test conditions: 500 ppm PEG, 30 psi, 77°F (25°C), 15% recovery, pH 8.0, 30 minutes operation. Individual element permeate flow may vary +/- 20%.

#### OPERATIONAL AND DESIGN DATA

Membrane Type .....	AUM Advanced Ultrafiltration Membrane
Configuration .....	Spiral Wound, Sanitary Style Element
Active Membrane Area .....	355 ft <sup>2</sup> (32.6 m <sup>2</sup> )
Typical Applied Pressure.....	30 - 60 psi (2 - 4 bar)
Maximum Applied Pressure .....	600 psi (41 bar)
Maximum Operating Temperature.....	122°F (50°C)
Feed pH Range .....	2 - 11 continuous
Chlorine Tolerance .....	5,000 ppm-days
Maximum Feed Flow .....	80 GPM (18 m <sup>3</sup> /hr)
Maximum Pressure Drop .....	15 psi (1 bar) per element; 60 psi (4 bar) across housing
Maximum SDI (15 minutes).....	5.0
Maximum Turbidity .....	1 NTU
Application .....	Water Purification for Beverages
Part Number .....	163040841
Replaces Models.....	8040-N6E6Q2



Element Weight: 50 lbs. (23 kg)

Length (A): 40.0" (1,016 mm) Diameter (B): 7.9" (200 mm) Permeate Tube (C): 1.125" (28.6 mm)

Permeate Tube: Polysulfone tube

Feed Spacer: 0.031" thick diamond spacer



Engineered Membrane  
**SOLUTIONS**

**LENNTech**

info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289