



PRODUCT SPECIFICATION


Low Fouling RO TurboClean® Element For Dialysis and High-Purity Applications

Model	Permeate Flow*	Average Salt Rejection	Minimum Salt Rejection
TurboClean® HP 4040-X20-F	2,400 GPD (9.1 m ³ /d)	99.5%	98.5%

* Performance is based on the following test conditions: 2,000 ppm NaCl, 225 psi, 77°F (25°C), 15% recovery, pH 8.0, 30 minutes operation. Individual element permeate flow may vary +/- 15%.

OPERATIONAL AND DESIGN DATA

Membrane Type	X-20™ Polyamide-Urea Advanced Composite Membrane
Configuration	Spiral Wound, Sanitary Style Element
Active Membrane Area	80 ft ² (7.4 m ²)
Typical Applied Pressure.....	150 - 300 psi (10 - 21 bar)
Maximum Applied Pressure	600 psi (41 bar)
Maximum Operating Temperature.....	113°F (45°C)
Feed pH Range	2 - 11 continuous
Chlorine Tolerance	<0.1 ppm
Maximum Feed Flow	20 GPM (4.5 m ³ /hr)
Maximum Pressure Drop	15 psi (1 bar) per element; 60 psi (4 bar) across housing
Maximum Feed SDI (15 minutes).....	5.0
Maximum Feed Turbidity	1 NTU
Application	High Purity Water
Part Number.....	194030442
Replaces Model(s).....	4040-N1P3U5



Element Weight:	15 lbs. (7 kg)		
Length (A):	40.0" (1,016 mm)	Diameter (B):	4.0" (101 mm)
Permeate Tube:	Desal Style tube; "Flush-ended" design		
Feed Spacer:	0.031" thick diamond spacer		
		Permeate Tube (C):	0.62" (15.9 mm)



Engineered Membrane
SOLUTIONS

LENNTECH

info@lennotech.com Tel. +31-152-610-900

www.lennotech.com Fax. +31-152-616-289