



PRODUCT SPECIFICATION

Heat-Sanitizable RO TurboClean® Element For Dialysis and High-Purity Applications

Model	Permeate Flow*	Average Salt Rejection	Minimum Salt Rejection
TurboClean® HP 8040-RO-HS	11,500 GPD (43 m ³ /d)	99.5%	98.5%

* Performance shown follows heat sanitization and is based on the following test conditions: 2,000 ppm NaCl, 225 psi, 77°F (25°C), 15% recovery, pH 8.0, 30 minutes operation. Individual element permeate flow may vary +/- 15%.

OPERATIONAL AND DESIGN DATA

Membrane Type	ACM Fully Aromatic Polyamide Advanced Composite Membrane
Configuration	Spiral Wound, Sanitary Style Element
Active Membrane Area	380 ft ² (35.3 m ²)
Typical Applied Pressure	150 - 300 psi (10 - 21 bar)
Maximum Applied Pressure	600 psi (41 bar)
Maximum Operating Temperature	113°F (45°C)
Maximum Sanitization Temperature	185°F (85°C) @ 25 psi maximum pressure
Feed pH Range	2 - 11 continuous
Chlorine Tolerance	<0.1 ppm
Maximum Feed Flow	80 GPM (18 m ³ /hr)
Maximum Pressure Drop	15 psi (1 bar) per element; 60 psi (4 bar) across housing
Maximum Feed SDI (15 minutes)	4.0
Maximum Feed Turbidity	1 NTU
Application	High Purity Water
Part Number	162080843



Element Weight: 50 lbs. (23 kg)

Length (A): 40.0+(1,016 mm) Diameter (B): 7.9+(200 mm) Permeate Tube (C): 1.125+(28.6 mm)

Permeate Tube: FilmTec Style tube

Feed Spacer: 0.028" thick diamond spacer



**Engineered Membrane
SOLUTIONS**

LENNTech

info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289