



PRODUCT SPECIFICATION


8" XN45 Sanitary TurboClean® Element

Model	Permeate Flow GPD (m³/day)*	Average Salt Rejection (%)	Minimum Salt Rejection (%)
TurboClean® NF 8038-XN45-31	9,000 (34)	95.0	92.0

* Performance is based on the following test conditions: 2,000 ppm MgSO₄, 110 psi, 77°F (25°C), 15% recovery, pH 8.0, 30 minutes operation. Individual element permeate flow may vary +/- 20%.

OPERATIONAL AND DESIGN DATA

Membrane Type	XN45 Advanced Polypiperazine Amide Nanofiltration Membrane
Configuration	Spiral Wound, Sanitary Element
Active Membrane Area	355 ft ² (33 m ²)
Typical Applied Pressure.....	200 - 400 psi (14 - 28 bar)
Maximum Applied Pressure	600 psi (41 bar)
Maximum Operating Temperature.....	122°F (50°C)
Feed pH Range	3 - 10 continuous
Chlorine Tolerance	<0.1 ppm
Maximum Feed Flow	100 GPM (23 m ³ /hr)
Maximum Pressure Drop.....	15 psi (1 bar) per element; 60 psi (4 bar) across housing
Replaces Model	8040-N2F7U8



Element Weight: 45 lbs. (20 kg)

Length (A): 38.0" (965 mm) Diameter (B): 7.9" (200 mm) Permeate Tube (C): 1.125" (28.6 mm)

Permeate Tube: FilmTec Style polysulfone tube; Interconnect and ATDs not included with element

Feed Spacer: 0.031" thick diamond spacer



**Engineered Membrane
SOLUTIONS**

LENNTech

info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289