



PRODUCT SPECIFICATION


6.3" ACM TurboClean® Element

Model	Permeate flow GPD (m3/day)*	Average Salt Rejection (%)	Minimum Salt Rejection (%)
TurboClean® RO 6338-ACM2-31	5,500 (20.0)	99.50	99.00

Performance is based on the following test conditions: 2,000 ppm NaCl, 225 psi, 25°C, 15% recovery, pH 8.0, 30 minutes operation.

OPERATIONAL AND DESIGN DATA

Membrane Type.....	ACM Fully Aromatic Polyamide Advanced Composite Membrane
Configuration.....	Spiral Wound, Sanitary Element
Active Membrane Area.....	225 ft ² (20.9 m ²)
Recommended Applied Pressure.....	Not applicable
Maximum Applied Pressure.....	600 psi (41 bar)
Maximum Operating Temperature.....	35 - 122°F (2 - 50°C)
Feedwater pH Range.....	2 - 11 continuous
Chlorine Tolerance.....	<0.1 ppm
Maximum Feed Flow.....	70 GPM (15.8 m ³ /hr)
Minimum Brine Flow/Permeate Flow Ratio....	5:1
Model Number Formerly.....	6338-M2C9U8
Application.....	Process



Element Weight : 33 (15)

Length (A) : 38.00 (965) Diameter (B) : 6.3 (160) Permeate Tube (C) : 1.14 (29.0)

Units in pounds and inches, units in parenthesis in kilograms and millimeters. Dim "A" does not include ATD.

Mechanical Configuration: Sanitary Style Core Tube ATD not included with element

Feed Spacer: 0.031" thick diamond spacer

* Permeate flow is clean water flux at standard conditions above. Not applicable for all feedwater conditions. Individual element's permeate flow may vary +/- 15%.



**Engineered Membrane
SOLUTIONS**

LENNTech

info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289