



DETAIL A

MODEL	A (mm)	B (mm)	C (mm)	VOLUME	WEIGHT(kg)	AREA (INSIDE)
18×65	2057 ± 15	1332	932	257	35	2.46 m ²

NOTE:

ADAPTOR

- 1. TEST METHOD FOR VESSEL PERFORMANCE COMPLIES WITH NSF/ANSI44-2002 "NSF INTERNATIONAL STANDARD/AMERICAN NATIONAL STANDARD"
- 2. MAXIMUM WORKING PRESSURE:10.5Bar, WATER MEDIUM TEMPERATURE RANGE: 1°C-49°C; NOT APPLICABLE TO CORROSIVE LIQUID;
- 3. DIMENSIONAL TOLERANCE: SJ1372-78, GRADE 8.
- 4. TANK IS SUPPLIED WITH ADAPTOR:

2"NPT MALE ADAPTOR / $1\frac{1}{2}$ "SOCKET ADAPTOR 2"BSP MALE ADAPTOR / 50MM SOCKET ADAPTOR

LENNTECH

info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

VERSION NO.			DESCRIPTION OF	CHANGES:			SIGNATURE	DATE	
	TIAL PLASTIC SHRINKA ESSARY):	AGE							
	SIGNATURE		₩ WAVE CYBER (SHANGHAI) CO., LTD.						
	NAME	DATE		WAVE CIDE	INGHAI) CO., LID.				
DESIGN			SCALE	MATERIAL		MODEL			
INSPECTION						DESCRIPTION 18" VESSEL (4"×4")			
APPROVAL THIS PRODUCT DRAWING CAN NOT BE COPIED AND/OR USED WITHOUT PRIOR WRITTEN APPROVAL OF WAVE CYBER.			QUANTITY	WEIGHT		(Threaded Side Inlets)			
			PROJECTION	COMPUTER CODE		DRAWING NO. 1141	82-00	VERSION NO.	
			DO NOT MEASURE THE DIMENSIONS. UNIT:		MM TOTAL PAGE: 1				