


Zeta Plus LP filter media is a depth filter composed of inorganic filter aid cationic resin and cellulose and is designed to be extremely low in extractables. The LP filter media is completely free of asbestos and glass microfibre.

Grade Selection

The Zeta Plus LP media is available in four grades.



Graphic 1 : Zeta Plus LP Grade Selection

In addition to the mechanical exclusion of particles by its depth loading feature, Zeta Plus LP media adsorbs contaminants too small for removal by mechanical sieving.

Features and Benefits

Depth filtration media designed to retain contaminants by mechanical entrapment and electro-kinetic adsorption

- High contaminant holding capacity for economical filtration and reliable particle removal

Full range of scaleable capsule and cartridge filter configurations

- Allows pilot testing and scale-up with the same materials that will be used in full-scale systems

FDA Drug Master File and USP Class VI Biological Safety

- Eases validation and regulatory submissions by providing vital documentation and traceability

Self-contained, single-use disposable capsule and cartridge modules

- Reduced labour time for change-outs and elimination of cleaning validation

Low LAL reactivity

- LP Filter medium is non-pyrogenic and is less likely to cause false positive results



Picture 1: Zeta Plus Family

Applications

Blood products

Antibiotics

Intravenous solutions

Growth media purification

Pharmaceutical and Bioprocess fluids

Diagnostics




Figure 1: Zeta Plus Cartridge Construction



Cartridge Construction


Zeta Plus LP Series filter media is available in both flat stock (sheets) and cartridges. Cartridges are constructed from individual cells. Each cell is constructed using polypropylene moulded edge seals and internal separators for high performance. The cells are assembled into a cartridge under a predetermined compression and made into a single unit by three 316 stainless steel bands with polypropylene cell separators. Various gasket materials are available depending upon application. Filter cartridges are available in 8, 12 and 16-inch diameters.

Capsule Construction

Zeta Plus LP Series filters are available in ready to use, fully disposable Zeta Plus BC capsules. The Zeta Plus BC capsule filters are completely encapsulated disposable filters for small volume filtration. Zeta Plus BC capsules are autoclavable and available in three sizes (25, 650 and 1300 cm² filtration area) to provide a high degree of application flexibility.

Efficient Flow Rates

The following graphs depict the flow rates for clean water and a 16 CPS fluid. Although the flow capacity is decreased by high viscosity solutions, an efficient flow rate can be achieved with proper media type selection. A maximum flow rate of 40 litres/m² is recommended to ensure optimal filter life and efficiency.



Graphic 2: Zeta Plus Flow Rate Graphs

Quality Control

Zeta Plus LP cartridges are manufactured in accordance with a strict quality assurance programme, following ISO regulation. Each media lot is sample audited for flow, density, charge capacity, organic and inorganic extractables and pyrogenicity. In addition, Zeta Plus LP cartridge packaging is labelled with a lot identification number to provide complete traceability.

Compatibility

The following table provides information about the diverse chemical compatibility of Zeta Plus LP media. *These recommendations are intended as a guide only.*

CHEMICALS	LP	GASKETS			
		Nitrile	Fluorocarbon	Ethylene Propylene	Silicone
Acetic Acid 5%-20%	G	G	G	G	G
Acetone 100%	G	P	G	G	G
Benzene	G	P	F	P	F
Carbon Tetrachloride Pure	G	F	G	P	F
Chloroethene	G	P	G	P	F
Chloroform - Dry	G	P	G	P	F
1,4 - Dioxane	G	P	P	P	P
DMF	G	F	P	P	No Data
Ethanol 10%	G	G	F	G	G
Ethanol 50%	G	G	F	G	G
Ethyl Acetate	G	P	P	P	F
n-Heptane	G	G	G	P	F
Hexane	G	G	G	P	F
1,1,1 - Trichloroethane	G	P	G	P	F
Lacquer thinner	G	G	G	P	F
Methanol	G	G	P	G	G
Methylene chloride (wet)	G	P	F	P	P
Methyl Ethyl Ketone (MEK)	G	P	P	G	G
Methyl Isobutyl Ketone (MIBK)	G	P	P	G	G
Paint thinner	G	P	G	P	G
Petroleum Ether	G	F	G	P	F
Sodium Hydroxide 20%	F	F	G	G	G
Toluene	G	P	G	P	F
Water (ambient)	G	G	G	G	G
Water (82°C)	G	G	G	G	G
Xylene	G	P	G	P	F

Explanation of ratings:
 G = Satisfactory - to maximum temperature given for material, unless restriction is noted.
 F = Fair - to maximum temperature given for material, unless restriction is noted.
 P = Not recommended.

Extractables

Zeta Plus LP media is designed to be extremely low in extractables. The following table provides the maximum amount of organic and inorganic compounds extracted from the Zeta Plus LP filter. A dynamic flow rinse was utilized to obtain the extractable values.

Operating Parameters

	Maximum Operating Pressure	Maximum Operating Temperature	Recommended Flush	Sterilisation Parameters	Maximum Flow Rate (FLUX) (in l/min per m²)
Standard and Special pre-coat Zeta Plus Cartridges	2.4 bar	82 °C	54 l/m² at 20 lpm/m²	autoclave or in-situ steam sterilisation for 1 hour at 121 °C	1.2 to 12
Zeta Plus BC25 Capsules	Inlet pressure: 2.75 bar Media pressure: 2.4 bar	40 °C	54 l/m² at 20 lpm/m²	Autoclave for 30 minutes at 121 °C (1 cycle)	1.2 to 12
Zeta Plus BC1000 and BC2000 Series Capsules	Inlet pressure: 5.5 bar at 25 °C 2.75 bar at 60 °C Media pressure: 2.4 bar	60 °C	54 l/m² at 20 lpm/m²	Autoclave for 30 minutes at 121 °C (up to 3 cycles)	1.2 to 12

Table 2: Zeta Plus LP series extractables (PPM) - Dynamic Flow Rinse

Extractable Rinse Volume (l/m²)	30 LP Series	60 LP Series	90 LP Series	
Calcium	1	0.037	0.800	0.790
	25	0.014	0.096	0.060
	50	0.094	0.012	0.009
	100	<0.001	<0.020	<0.001
Magnesium	1	0.880	1.800	2.600
	25	0.140	0.220	0.770
	50	<0.001	0.016	<0.001
	100	0.013	<0.020	0.029
Sodium	1	1.700	4.600	8.500
	25	<0.001	1.900	4.200
	50	<0.001	<0.001	<0.001
	100	<0.001	0.600	<0.001
Potassium	1	0.002	0.026	0.002
	25	0.001	0.002	0.002
	50	<0.001	0.001	0.001
	100	<0.001	0.001	<0.001
Iron	1	0.068	0.250	0.230
	25	0.012	0.031	0.016
	50	0.002	0.015	0.007
	100	<0.001	0.005	0.003
Zinc	1	0.008	0.026	0.031
	25	0.007	0.008	0.007
	50	<0.001	0.013	0.005
	100	<0.001	<0.001	<0.001
Aluminium	1	0.112	0.330	1.400
	25	0.037	0.049	0.099
	50	0.006	0.009	0.018
	100	0.002	0.002	0.088
Manganese	1	0.009	0.026	0.079
	25	<0.001	0.017	0.013
	50	<0.001	<0.001	<0.001
	100	<0.001	<0.001	<0.001
Silica	1	0.070	0.200	0.260
	25	0.010	0.022	0.070
	50	<0.001	<0.001	0.005
	100	0.002	<0.001	<0.001
Copper	1	0.002	0.009	0.033
	25	<0.001	0.002	0.001
	50	<0.001	<0.001	<0.001
	100	<0.001	<0.001	<0.001
Nickel	1	0.004	0.020	0.019
	25	0.001	0.003	0.002
	50	0.001	<0.001	0.002
	100	0.002	0.001	<0.001
Chromium	1	<0.001	<0.001	0.002
	25	<0.001	<0.001	<0.001
	50	<0.001	<0.001	<0.001
	100	<0.001	<0.001	<0.001

Not detected: Co, Mo and Ag.

Zeta Plus LP Series Ordering Guide

1. Cartridges

Zeta Plus	Diameter (inch)	Cartridge Design	Gasket Type	Grade	Formulation	
Z	08	P = Plug-in 7 cells (0.23 m ²)	Standard A = Silicone (MVQ)*	30 50 60 90	LP Resin S	
		D = Standard 8 cells (0.26 m ²)	Standard D = Nitrile (NBR)*			
	12	C = 9 cells / small (0.85 m ²) B = Special precoat 12 cells (1.1 m ²) D = Standard 16 cells (1.5 m ²) S = Special 7 cells (0.7 m ²)	Options A = Silicone (MVQ)* B = Fluorocarbon (FPM)* C = EPR (EPDM)*			
		16	M = Standard diffusion netting 14 cells (3.2 m ²) D = Standard 15 cells (3.4 m ²) S = Special precoat 9 cells (2.1 m ²)			*ISO Designation

2. Zeta Plus BC Capsules

Catalogue Number	Grade and Formulation
BC 0025L (Luer) - 25 cm ² area BC 0025S (Sanitary) - 25 cm ² area BC 1000A (single pack) - 650 cm ² area BC 1000B (3-pack) - 650 cm ² area BC 2000A (single pack) - 1300 cm ² area BC 2000B (3-pack) - 1300 cm ² area	30 LP 50 LP 60 LP 90 LP

Important Notice

3M Purification MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Since a variety of factors can affect the use and performance of a 3M Purification product in a particular application, some of which are uniquely within the user's knowledge and control, user is responsible for determining whether or not the 3M Purification product is fit for a particular purpose and suitable for user's method of application.

Limited Warranty

3M Purification warrants this product to be free from defects in material and workmanship during normal use for a period of one (1) year from the date of shipment from the factory. If the Product(s) is (are) defective within this warranty period, your exclusive remedy and 3M Purification's sole obligations shall be, at 3M Purification's option, to replace or repair the Product(s) or refund the original purchase price of the Product(s). This warranty does not apply to failures that result from abuse, misuse, alteration or damage not caused by 3M Purification or failure to properly follow installation and use instructions.

Limitation of Liability: 3M Purification will not be liable for any loss or damage arising from the use of the Product(s), whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you.

This warranty gives you specific legal rights and you may have other rights which vary from state to state, or country to country.

Zeta Plus and 3M are trademarks of 3M used under license.

LENNTECH

info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289



Data may be subject to change without further notice.

© 3M 2010. All rights reserved.

v.2 - DOC10014
LITCTZPLP1.EU - 1110

Z 08 P A 30 LP	Z 16 M A 30 LP	Z 12 B D 50 LP	BC 0025L 30 LP
Z 08 P A 50 LP	Z 16 M A 50 LP	Z 12 B D 60 LP	BC 0025L 50 LP
Z 08 P A 60 LP	Z 16 M A 60 LP	Z 12 B D 90 LP	BC 0025L 60 LP
Z 08 P A 90 LP	Z 16 M A 90 LP	Z 12 D A 30 LP	BC 0025L 90 LP
Z 08 D A 30 LP	Z 16 M B 30 LP	Z 12 D A 50 LP	BC 0025S 30 LP
Z 08 D A 50 LP	Z 16 M B 50 LP	Z 12 D A 60 LP	BC 0025S 50 LP
Z 08 D A 60 LP	Z 16 M B 60 LP	Z 12 D A 90 LP	BC 0025S 60 LP
Z 08 D A 90 LP	Z 16 M B 90 LP	Z 12 D B 30 LP	BC 0025S 90 LP
Z 08 D D 30 LP	Z 16 M C 30 LP	Z 12 D B 50 LP	BC 1000A 30 LP
Z 08 D D 50 LP	Z 16 M C 50 LP	Z 12 D B 60 LP	BC 1000A 50 LP
Z 08 D D 60 LP	Z 16 M C 60 LP	Z 12 D B 90 LP	BC 1000A 60 LP
Z 08 D D 90 LP	Z 16 M C 90 LP	Z 12 D C 30 LP	BC 1000A 90 LP
Z 08 D B 30 LP	Z 16 M D 30 LP	Z 12 D C 50 LP	BC 1000B 30 LP
Z 08 D B 50 LP	Z 16 M D 50 LP	Z 12 D C 60 LP	BC 1000B 50 LP
Z 08 D B 60 LP	Z 16 M D 60 LP	Z 12 D C 90 LP	BC 1000B 60 LP
Z 08 D B 90 LP	Z 16 M D 90 LP	Z 12 D D 30 LP	BC 1000B 90 LP
Z 08 D C 30 LP	Z 16 D A 30 LP	Z 12 D D 50 LP	BC 2000A 30 LP
Z 08 D C 50 LP	Z 16 D A 50 LP	Z 12 D D 60 LP	BC 2000A 50 LP
Z 08 D C 60 LP	Z 16 D A 60 LP	Z 12 D D 90 LP	BC 2000A 60 LP
Z 08 D C 90 LP	Z 16 D A 90 LP	Z 12 S A 30 LP	BC 2000A 90 LP
Z 12 C A 30 LP	Z 16 D B 30 LP	Z 12 S A 50 LP	BC 2000B 30 LP
Z 12 C A 50 LP	Z 16 D B 50 LP	Z 12 S A 60 LP	BC 2000B 50 LP
Z 12 C A 60 LP	Z 16 D B 60 LP	Z 12 S A 90 LP	BC 2000B 60 LP
Z 12 C A 90 LP	Z 16 D B 90 LP	Z 12 S B 30 LP	BC 2000B 90 LP
Z 12 C B 30 LP	Z 16 D C 30 LP	Z 12 S B 50 LP	Z 16 S B 30 LP
Z 12 C B 50 LP	Z 16 D C 50 LP	Z 12 S B 60 LP	Z 16 S B 50 LP
Z 12 C B 60 LP	Z 16 D C 60 LP	Z 12 S B 90 LP	Z 16 S B 60 LP
Z 12 C B 90 LP	Z 16 D C 90 LP	Z 12 S C 30 LP	Z 16 S B 90 LP
Z 12 C C 30 LP	Z 16 D D 30 LP	Z 12 S C 50 LP	Z 16 S C 30 LP
Z 12 C C 50 LP	Z 16 D D 50 LP	Z 12 S C 60 LP	Z 16 S C 50 LP
Z 12 C C 60 LP	Z 16 D D 60 LP	Z 12 S C 90 LP	Z 16 S C 60 LP
Z 12 C C 90 LP	Z 16 D D 90 LP	Z 12 S D 30 LP	Z 16 S C 90 LP
Z 12 C D 30 LP	Z 16 S A 30 LP	Z 12 S D 50 LP	Z 16 S D 30 LP
Z 12 C D 50 LP	Z 16 S A 50 LP	Z 12 S D 60 LP	Z 16 S D 50 LP
Z 12 C D 60 LP	Z 16 S A 60 LP	Z 12 S D 90 LP	Z 16 S D 60 LP
Z 12 C D 90 LP	Z 16 S A 90 LP	Z 12 B B 60 LP	Z 16 S D 90 LP
Z 12 B A 30 LP	Z 12 B A 90 LP	Z 12 B B 90 LP	Z 12 B C 50 LP
Z 12 B A 50 LP	Z 12 B B 30 LP	Z 12 B C 30 LP	Z 12 B C 60 LP
Z 12 B A 60 LP	Z 12 B B 50 LP	Z 12 B D 30 LP	Z 12 B C 90 LP