






3M[™] Liqui-Cel[™] SP-1×3 Series Membrane Contactor

Typical Properties

| Membrane Characteristics | | |
|-------------------------------|--|---|
| Cartridge Configuration | No Baffle Radial Flow | |
| Liquid Flow Guidelines | 15 - 60 ml/min (Liquid must flow on the shellside) | |
| Membrane Type | UP | UP II |
| Membrane Type | Recommended for low surface tension liquids that are water-based | Recommended for low surface tension fluids with aggressive formulations |
| Membrane/Potting Material | Polyolefin / Polyethylene | |
| Typical Membrane Surface Area | 294 cm² | |
| Priming Volume (approximate) | | |
| Shellside | 15 ml | |




| Pressure Guidelines* | |
|---|--|
| Maximum Shellside <u>LIQUID</u> Working Temperature/ Pressure | 5-25°C, 3.1 barg (41-77°F, 45 psig) 40°C, 1.0 barg (104°F, 15 psig) |
| Working reinperature/ Fressure | +0 0, 1.0 burg (10+ 1, 10 psig) |

^{*} Note: Liquid pressure should always exceed gas pressure.

| Housing Characteristics | | |
|---------------------------------|--|--|
| Material | Black Polyethylene | |
| Connections | | |
| Shellside (Liquid Inlet/Outlet) | ¼ inch NPT Male Standard Female Luer Lock | |
| Lumenside (vacuum) | % inch NPT Male Standard Female Luer Lock | |

| Weight (approximate) | |
|----------------------|----------|
| Dry | 28 grams |
| Water-filled | 43 grams |




All dimensions are nominal values. Refer to 3M.com/Liqui-Cel for detailed housing drawings.

Regulatory


Complies with the limits as set by RoHS Directive 2011/65/EU Annex II; recasting 2002/95/EC. Constructed of FDA CFR title 21 compliant materials for wetted parts only at ambient temperatures.

3M™ Liqui-Cel™ SP-1×3 Series Membrane Contactor



- UP

— UP II



Test condition O₂ Removal: Vacuum mode with water at 35°C. Vacuum: 50 torr

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M and Liqui-Cel are trademarks of 3M Company. All other trademarks are the property of their respective owners. © 2017 3M Company. All rights reserved.



ISO 9001



LENNTECH

info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

LC-1019 Rev. 03/2017