

AWC[®] A-109

RO Membrane Antiscalant for High Calcium Carbonate

ADVANTAGES

- Designed to inhibit inorganic scale formation in membrane separation processes
- Inhibits calcium carbonate scale up to a Calcium Carbonate Nucleation Index (CCNI) of 2.3
- Helps reduce or eliminate acid dosing in RO/NF feedwaters that contain high alkalinity, even when operating at recoveries $\geq 90\%$
- Effectively stabilizes metal ions and disperses insoluble metal oxides in the reject
- Controls calcium fluoride, calcium sulfate, barium sulfate and strontium sulfate scales in waters with a high fouling potential
- Environmentally compatible, especially where discharge of waste into the environment is a concern
- Certified by NSF to NSF/ANSI Standard 60

TYPICAL PROPERTIES

Appearance	Clear light yellow to amber liquid
Odor	Characteristic
Solubility in water	Complete
pH (as is) @ 25°C	< 2.0
Specific Gravity	1.20 \pm 0.05

PACKAGING

5 gallon pails, 55 gallon non-returnable plastic drums, 275 gallon totes and bulk shipments

SAFETY & HANDLING

Store in a cool, dry place. In accordance with good safety practice, handle with care and avoid contact with eyes and prolonged or repeated contact with skin. For more information, see the Safety Data Sheet provided with this product.

CHEMICAL FEEDING AND CONTROL

Normally fed continuously prior to the final cartridge filter. It should be injected by chemical dosing pump from a dilution tank or directly from the drum to the feedwater line. The amount of AWC A-109 required to inhibit scale formation depends on the quality of feedwater and size of the membrane system. If product needs to be diluted, do not exceed a 10X dilution to prevent over-dilution of the food grade preservatives.

LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289

