

# CA AX polyester felt filtering medium and granular activated carbon - 25 micron throw-away cartridge



**APPLICATIONS**

**Pre-Filtration and elimination of:** unpleasant odours and flavours from water caused by chlorine and other organic substances; removal of pesticides, insecticides, chlorinate solvents.

**Domestic use:** filtration and anti-chlorine treatment in point-of-entry appliances and in point-of-use appliances: washing machines, showers and drinking water units.

**Technical use:** anti-chlorine treatment in alimentary, chemical and pharmaceutical industry, pre-treatment for the protection of reverse osmosis units.

**Average life-span:** 3 months.

**Maintenance:** none.

**WORKING CONDITIONS**

Max working temperature \_\_\_\_\_ 45°C

**SPECIFICATIONS**

Non toxic materials, suitable for drinking water.


**Filtering medium:** polyester felt.

**End caps and grid:** polypropylene.

**O-rings:** ETP.

**Treating material:** granular activated carbon of coconut shell.

suitable housing	cartridge model	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	CA 5 AX 25 mcr	5"	125	70	25	300
Junior	CA 7 AX 25 mcr	7"	173	70	25	450
Senior	CA 10 AX 25 mcr	10"	250	70	25	600
Master	CA 20 AX 25 mcr	20"	505	70	25	1200



**VARIANTS** available on minimum quantity

**AG** Cartridges with granular activated carbon silver treated for bacteriostatic action.

**KDF** Cartridges with KDF® for reduction of heavy-metals.

# LA AX container with granular activated carbon throw-away cartridge



**APPLICATIONS**

**Elimination of:** unpleasant odours and flavours from water caused by chlorine and other organic substances; removal of pesticides, insecticides, chlorinate solvents.

**Domestic use:** anti-chlorine treatment in point-of-entry appliances and in point-of-use appliances: washing machines, showers and drinking water units.

**Technical use:** anti-chlorine treatment in alimentary, chemical and pharmaceutical industry, pre-treatment for the protection of reverse osmosis units.

**Average life-span:** 3 months.

**Maintenance:** none.

**WORKING CONDITIONS**

Max working temperature \_\_\_\_\_ 45°C

**SPECIFICATIONS**

Non-toxic materials, suitable for drinking water.

**Container:** polystyrene.

**End cap and grid:** polystyrene.


**O-rings:** ETP.

**Containing sponge:** polyurethane.

**Treating material:** granular activated carbon of coconut shell.

**Remark** - Use a pre-filter to protect the cartridge.

suitable housing	cartridge model	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	LA 5 AX-TS	5"	127	72	25	400
Junior	LA 7 AX-TS	7"	183	72	25	400
Senior	LA 10 AX-TS	10"	252	72	25	400
Master	LA 20 AX-TS	20"	510	72	25	400



**VARIANTS** available on minimum quantity

Cartridges with different heights.

**AG** Cartridges with granular activated carbon silver treated for bacteriostatic action.

**KDF** Cartridges with KDF® for reduction of heavy-metals.

Cartridges with opaque container.

**LENNTECH**

info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289