

FA AX wound thread filtering medium - from 1-3 to 100 micron throw-away cartridge



APPLICATIONS

Filtration of: sand, scale, lime, rust, fine particles.
Domestic use: filtration of drinking water, protection of taps, boilers, washing machines and other installations.
Technical use: pre-filtration for water-pumps, irrigations systems, protection of industrial installations; filtration of water and other liquids in industrial applications: chemical, petrochemical, photographic, electroplating, pharmaceutical.
Average life-span: from 3 to 6 months.
Maintenance: none.

WORKING CONDITIONS


Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
Filtering medium: polypropylene thread.
Inner core: polypropylene.
End caps: polypropylene.
O-rings: ETP.



suitable housing	cartridge model	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	FA 5 AX	5"	125	61	25	500
Junior	FA 7 AX	7"	173	61	25	700
Senior	FA 10 AX	10"	250	61	25	1000
Master	FA 20 AX	20"	505	61	25	2000



Available filtration rates, in micron (mcr)
 1-3 mcr 5 mcr 10 mcr 25 mcr 50 mcr 100 mcr

VARIANTS available on minimum quantity

CA Cartridges with granular activated carbon.

CA-AG Cartridges with granular activated carbon silver treated for bacteriostatic action.

CA-KDF Cartridges with granular activated carbon and KDF® for reduction of heavy-metals.

GA AX quartzite filtering medium - 10 micron throw-away cartridge



APPLICATIONS

Filtration of: lime, rust, fine particles.
Domestic use: filtration of drinking water, protection of taps, boilers, washing machines and other installations.
Technical use: filtration for irrigation systems, protection of industrial installations, fine filtration of liquids.
Average life-span: about 6 months.
Maintenance: none.

WORKING CONDITIONS


Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
Filtering medium: conglomerate of quartzite granules, self-supporting frame.
End caps: polypropylene.
O-rings: ETP.



suitable housing	cartridge model	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	GA 5 AX 10 mcr	5"	125	70	25	500
Junior	GA 7 AX 10 mcr	7"	173	70	25	700
Senior	GA 10 AX 10 mcr	10"	250	70	25	1000
Master	GA 20 AX 10 mcr	20"	505	70	25	2000



VARIANTS available on minimum quantity

Cartridges with different filtration rates.

LENNTECH

info@lennotech.com Tel. +31-152-610-900
 www.lennotech.com Fax. +31-152-616-289