

# RA BX stainless steel filtering net - 70 micron washable cartridge



### APPLICATIONS

**Filtration of:** sand, scale, rust.  
**Domestic use:** filtration of drinking water, protection of taps, boilers, washing machines and other installations.  
**Technical use:** pre-filtration for water-pumps, irrigations systems, protection of industrial installations; filtration of brackish water (only RA-A stainless steel AISI 316 type).  
**Average life-span:** RA-A about 5 years, RA-C about 3 years.  
**Maintenance:** wash every 3 months.

### WORKING CONDITIONS

Max working temperature \_\_\_\_\_ 45°C


### CARATTERISTICHE

Non-toxic materials, suitable for drinking water.  
**Filtering medium:** stainless steel net AISI 316 or AISI 304.  
**Inner armouring:** stainless steel AISI 316 or AISI 304.  
**Inner core:** polypropylene.  
**End caps:** polypropylene.  
**O-rings:** ETP.

suitable housing	cartridge RA-A AISI 316	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	RA 5-A BX 70 mcr	5"	125	70	32	800
Junior	RA 7-A BX 70 mcr	7"	173	70	32	1100
Senior	RA 10-A BX 70 mcr	10"	250	70	32	1600
Master	RA 20-A BX 70 mcr	20"	505	70	32	3000

suitable housing	cartridge RA-C AISI 304	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	RA 5-C BX 70 mcr	5"	125	70	32	800
Junior	RA 7-C BX 70 mcr	7"	173	70	32	1100
Senior	RA 10-C BX 70 mcr	10"	250	70	32	1600
Master	RA 20-C BX 70 mcr	20"	505	70	32	3000



**VARIANTS** available on minimum quantity

Cartridges with different filtration rates.

# SA BX pleated stainless steel filtering net - 50 micron washable cartridge



### APPLICATIONS

**Filtration of:** sand, scale, rust.  
**Domestic use:** filtration of drinking water, protection of taps, boilers, washing machines and other installations.  
**Technical use:** pre-filtration for water-pumps, irrigations systems, protection of industrial installations; filtration of brackish water (only SA-A stainless steel AISI 316 type).  
**Average life-span:** SA-A about 5 years, SA-C about 3 years.  
**Maintenance:** wash every 3 months.

### WORKING CONDITIONS

Max working temperature \_\_\_\_\_ 45°C


### SPECIFICATIONS

Non-toxic materials, suitable for drinking water.  
**Filtering medium:** stainless steel net AISI 316 or AISI 304.  
**Inner core:** polypropylene.  
**End caps:** polypropylene.  
**O-rings:** ETP.

suitable housing	cartridge SA-A AISI 316	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	SA 5-A BX 50 mcr	5"	125	70	32	1100
Junior	SA 7-A BX 50 mcr	7"	173	70	32	1500
Senior	SA 10-A BX 50 mcr	10"	250	70	32	2200
Master	SA 20-A BX 50 mcr	20"	505	70	32	3800

suitable housing	cartridge SA-C AISI 304	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	SA 5-C BX 50 mcr	5"	125	70	32	1100
Junior	SA 7-C BX 50 mcr	7"	173	70	32	1500
Senior	SA 10-C BX 50 mcr	10"	250	70	32	2200
Master	SA 20-C BX 50 mcr	20"	505	70	32	3800



**VARIANTS** available on minimum quantity

Cartridges with different filtration rates.