

TS AX pleated polyester fabric filtering medium - 50 micron washable cartridge



APPLICATIONS

Filtration of: sand, scale, rust.
Domestic use: filtration of drinking water, protection of taps, boilers, washing machines and other installations.
Technical use: pre-filtration for water-pumps, irrigations systems, protection of industrial installations.
Average life-span: about 24 months.
Maintenance: wash every 3 months.


WORKING CONDITIONS

Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
Filtering medium: polyester fabric.
Inner core: polypropylene.
End caps: polypropylene.
O-rings: ETP.

suitable housing	cartridge model	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	TS 5 AX 50 mcr	5"	125	70	25	1100
Junior	TS 7 AX 50 mcr	7"	173	70	25	1500
Senior	TS 10 AX 50 mcr	10"	250	70	25	2200
Master	TS 20 AX 50 mcr	20"	505	70	25	3800



VARIANTS available on minimum quantity

Cartridges with different filtration rates.

CS AX pleated special paper filtering medium - 25 micron throw-away cartridge



APPLICATIONS

Filtration of: sand, scale, lime, rust.
Domestic use: filtration of drinking water, protection of taps, boilers, washing machines and other installations.
Technical use: pre-filtration for water-pumps, irrigations systems, protection of industrial installations.
Average life-span: about 6 months.
Maintenance: none.


WORKING CONDITIONS

Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
Filtering medium: special paper.
Inner core: polypropylene.
End caps: polypropylene.
O-rings: ETP.

suitable housing	cartridge model	cartridge height	mm			recommended flow rate l/h
			A	B	C	
Medium	CS 5 AX 25 mcr	5"	125	70	25	1000
Junior	CS 7 AX 25 mcr	7"	173	70	25	1400
Senior	CS 10 AX 25 mcr	10"	250	70	25	2000
Master	CS 20 AX 25 mcr	20"	505	70	25	3500



VARIANTS available on minimum quantity

Cartridges with different filtration rates.