



Notes:

1. All dimensions are for reference only, not for construction unless certified.
2. * - *Item 14 & 15 are optional. Delivered upon request.*
Priced separately.
3. Drawing unit: mm. (inches).
4. Saddles can be shimmed if required.
5. Do not scale drawing, may be reprinted on any paper size or copied.
6. The vessel is supplied with two strap assembly.
7. For further information please contact BEL

- Table №1 for membrane length 21" (533.4mm.).
- Table №2 for membrane length 40" (1016mm.).

Warning.

1. Never pressurize a pressure vessel that was not loaded with membrane elements.
2. Wrong manifolding may cause an excessive pressure on port what can lead to leaks.
3. Max. allowable working pressure not to exceed 300 psi. (20.7 bar).
4. Permeate internal pressure not to exceed 125 psi. (8.6 bar).
5. Operating temperature not to exceed 49°C (120°F).

Item	Part number	Q-ty	Title	Material
1	41300-0	1	Body of Pressure Vessel	Glass/Epoxy
2	55410208	2	Retaining ring	316 stainless steel
3	003-400-0005	2	Base plate	Engineering plastic
4	55412360	2	Seal for base plate	EPDM
5	55412377	0-6	Disk spacer	Engineering plastic
6	As required	2	Membrane seal	EPDM
7	As required	2	Adapter	Engineering plastic
8	55412367	2	Seal for Adapter	EPDM
9	009-106-0450	2	F/C Port	316 stainless steel
10	014-100-0505	2	Seal for F/C Port	EPDM
11	006-112-1202	2	Disk for F/C Port	304 stainless steel
12	011-100-1202	2	Retaining ring	316 stainless steel
13	55412368	2	Retaining ring	316 stainless steel

-Vessel support parts -optional -

14 *	55410352	2-3	Saddle	Engineering plastic
15 *	55410246	2	Strap	316 stainless steel

BEL	TITLE	BEL 4-S-300 psi. RO PRESSURE VESSEL	DESIGN	NAME	DATE
			CHECK	Yuri V.	30/07/2014
DRAWING No.	BEL 4-S-300		APPR.	Ari A.	30/07/2014
THIS DRAWING IS PROPERTY OF BEL GROUP LIMITED IT IS STRICTLY FORBIDDEN TO USE, COPY, REPRODUCE OR DISCLOSE ANY PART OF IT TO THIRD PARTY WITHOUT WRITTEN AUTHORIZATION.					REV.: 4