Belclene® 108





Antiscalant Designed for Multi-Purpose Deposit Control for Industrial Process Environments

Description

Belclene 108 is a neutralized, aqueous solution of a polyacrylic polymer that delivers multi- purpose deposit control properties required in process water environments.

Uses

Belclene 108:

- Provides effective inhibition of the common types of scale encountered in Industrial environments e.g. in sugar juice evaporators
- Continues to inhibit scale formation at hot heat transfer surfaces e.g. evaporators, boilers & food processing plants
- Belclene 108 is FDA approved for cane and beet processing (173.73). Belclene 108 is Kosher certified.

Benefits

Belclene 108 provides effective deposit control where consecutive evaporation of process water will develop differential scaling potentials. Deposits of; oxalate, carbonate, sulfate and phosphate might otherwise develop. Belclene 108 programs will maximize heat transfer efficiency by minimizing these fouling problems.

Usage

*Please consult with your BWA Water Additives representative to determine optimal dosage recommendations for your system.

Packaging / Weight

Drums 551 lb 250 kg IBCs/Totes 2,866 lb 1,300 kg

Physical Properties

Appearance Slightly viscous liquid,

colorless to pale yellow

Total solids 42% w/w
Specific gravity 1.31 at 20°C
pH 8 at 20°C

Boiling range 100°C (212°F)

Further details are available in the safety data sheet

^{*}Consult your sales representative for availability.



info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Patents:

BWA Water Additives (BWA) owns or is the licensee of patents and patent applications, which may cover the products and/or uses described in this brochure.

The following are registered trademarks of BWA Belclene, Belcor, Belgard, Belite, Bellacide, Bellasol, Belsperse, BromiCide, Flocon, Geogard and Liquibrom Drop and Swirl logo.
® Registered US Patent and Trademark Office. © 2017 BWA, All rights reserved.

The information contained in this product sheet is based on data available to BWA Water Additives at the time of publication. While BWA has made every effort to ensure this information is correct, no responsibility can be accepted by BWA for any loss or liability occasioned by any person acting or refraining from acting as a result of the contents of this publication. BWA cannot guarantee that the results described in this information will be achieved by others if BWA has not participated in the testing process. BWA therefore makes no warranty of merchantability or fitness for a particular purpose or any express or implied warranty in respect of this information. This information is intended for use by technically trained personnel at their discretion and risk and is not a substitute for specific professional or technical advice. BWA's liability shall be limited by its standard limitations of liability contained within its standard terms and conditions of sale if BWA makes any sales to you.

© 2017 all rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means or stored in any retrieval system without the prior written permission of BWA Water Additives UK Limited. BWA Water Additives UK Limited is a private limited company registered in England and Wales at 2 Brightgate Way, Manchester M32 0TB, Registered No. 5657343.