Belclene® 400





Multifunctional Deposit Control Agent for Industrial Water

Description

Belclene 400 is a multifunctional deposit control agent that provides great flexibility in developing phosphonate-based corrosion control formulations for cooling water, process water, and similar applications.

Application

Formulations with Belclene 400 provide:

- Phosphate inhibition/dispersancy and calcium phosphonate stabilization
- Iron oxide dispersancy
- Zinc stabilization
- Calcium carbonate inhibition
- Halogen stability
- FDA and USDA approvals

Benefits

Belclene 400 has unique properties of that allow it to be to be used not only for general calcium phosphate and calcium carbonate fouling, but also as a building block to improve the performance of phosphate, polyphosphate, phosphonate and zinc based water treatment formulations.

Usage

*Please consult with your BWA Water Additives representative to determine optimal dosage recommendations for your system.

Packaging / Weight

Drum 528 lb 240 kg
IBCs/Totes 2,650 lb 1,225 kg

* Bulk quantities available. Consult your sales representative for availability.

Physical Properties

Appearance	Clear to pale yellow liquid
Odor	Slight
Solids content	47 – 53 %w/w
Specific gravity	1.24 @ 20 °C
pH of undiluted	2.5 @ 20 °C
product	
Viscosity	250mm ² /s @ 25 °C
Boiling point range	103-105°C (217-221°F)
Freezing point	-12 to -3°C (10-28°F)
Theoretical	<1%
phosphorus	
Content (as P)	
Solubility in:	

-Water Miscible
-Ethylene glycol Miscible

-Methanol Miscible (solution becomes turbid over the concentration range

of 5-60%)

-50% caustic soda Miscible

Further details are available in the safety data sheet



info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Patents:

BWA Water Additives (BWA) owns or is the licensee of patents and patent applications, which may cover the products and/or uses described in this brochure.

The following are registered trademarks of BWA Belclene, Belcor, Belgard, Belite, Bellacide, Bellasol, Belsperse, BromiCide, Flocon, Geogard and Liquibrom Drop and Swirl logo. ® Registered US Patent and Trademark Office. © 2016 BWA all rights reserved.

The information contained in this product sheet is based on data available to BWA Water Additives at the time of publication. While BWA has made every effort to ensure this information is correct, no responsibility can be accepted by BWA for any loss or liability occasioned by any person acting or refraining from acting as a result of the contents of this publication. BWA cannot guarantee that the results described in this information will be achieved by others if BWA has not participated in the testing process. BWA therefore makes no warranty of merchantability or fitness for a particular purpose or any express or implied warranty in respect of this information. This information is intended for use by technically trained personnel at their discretion and risk and is not a substitute for specific professional or technical advice. BWA's liability shall be limited by its standard limitations of liability contained within its standard terms and conditions of sale if BWA makes any sales to you.

© 2016 all rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means or stored in any retrieval system without the prior written permission of BWA Water Additives UK Limited. BWA Water Additives UK Limited is a private limited company registered in England and Wales at 2 Brightgate Way, Manchester M32 0TB, Registered No. 5657343.