Bellacide® 355





Innovative Non-Oxidizing Biocide for Industrial Water Systems

Description

Bellacide 355 is a high performance broad spectrum biocide, which is fast acting, long lasting with superior activity compared to other non-oxidizing biocides.

Application

Bellacide 355 is a concentrated 5% active nonoxidizing biocide containing tributyl tetradecyl phosphonium chloride (TTPC):

- Cost effective, broad spectrum of activity effective against aerobic bacteria (including Legionella pneumophila), anaerobic bacteria, algae and fungi.
- Good cleaning action due to surface active properties and low foaming properties make it suitable for cleaning cooling systems, which are heavily fouled with microbiological slimes.
- Highly effective against problematic organisms.
- Compatible and easy to use across a broad pH range. Bellacide 355 is not affected by the pH of the system water (pH 5 to 12) and can be used with oxidizing agents such as chlorine.
- No contribution to TOC loading and filtration aid in closed loop systems because re-growth is dramatically reduced and Bellacide 355 does not contribute to the total organic carbon (TOC) load.
 ** Legionella control is based on an independent third party lab, and not a guarantee of results in field use.

Benefits

Bellacide 355 is a high performing multifunctional surface active biocide for industrial water systems, which is compatible with halogens and provides a low cost treatment for open and closed cooling systems.

Usage

Typical Dosage: 250 ppm

*Please consult with your BWA Water Additives representative to determine optimal dosage recommendations for your system.

Packaging / Weight

Pail	42 lb	19 kg
Drum	450 lb	200 kg
IBCs/Totes	2,750 lb	1,000 kg

^{*}Consult your sales representative for availability.

Physical Properties

Appearance	Clear, colorless liquid	
Odor	Slight	
Active content	4.9-5.1% w/w	
Specific gravity	0.98-1 at 20/20°C	
pH of undiluted	6.0-8.0 at 20°C	
product		
Viscosity	55-65mm ² /s at 25°C	
Boiling range	100°C (212°F)	
(760 mm Hg)		
Solubility in:		
- Water	Ready Soluble	
 pH limitations 	2-12	

Further details are available in the safety data sheet



info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Patents:

BWA Water Additives (BWA) owns or is the licensee of patents and patent applications, which may cover the products and/or uses described in this brochure.

The following are registered trademarks of BWA Belclene, Belcor, Belgard, Belite, Bellacide, Bellasol, Belsperse, BromiCide, Flocon, Geogard and Liquibrom Drop and Swirl logo. ® Registered US Patent and Trademark Office. © 2016 BWA all rights reserved.

The information contained in this product sheet is based on data available to BWA Water Additives at the time of publication. While BWA has made every effort to ensure this information is correct, no responsibility can be accepted by BWA for any loss or liability occasioned by any person acting or refraining from acting as a result of the contents of this publication. BWA cannot guarantee that the results described in this information will be achieved by others if BWA has not participated in the testing process. BWA therefore makes no warranty of merchantability or fitness for a particular purpose or any express or implied warranty in respect of this information. This information is intended for use by technically trained personnel at their discretion and risk and is not a substitute for specific professional or technical advice. BWA's liability shall be limited by its standard limitations of liability contained within its standard terms and conditions of sale if BWA makes any sales to you.

© 2016 all rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means or stored in any retrieval system without the prior written permission of BWA Water Additives UK Limited. BWA Water Additives UK Limited is a private limited company registered in England and Wales at 2 Brightgate Way, Manchester M32 0TB, Registered No. 5657343.