Belsperse® 164





High Performance Dispersant for Deposit Control and Removal

Description

Belsperse 164 provides greater flexibility and better performance in developing multiple antiscalant programs for a variety of scales found in boiler systems, foods plants, and cleaning applications.

Benefits

Belsperse 164 is a multifunctional product that provides the benefits of many separate products, including:

- Excellent calcium phosphate, calcium carbonate, silicate and iron oxide dispersancy all in a single product
- Better deposit control and thermal stability than methacrylates, acrylates, and copolymers
- FDA approved for use in applications where steam may contact food
- Wide application range across industries, for both online and offline system protection and system clean ups

Usage

*Please consult with your BWA Water Additives representative to determine optimal dosage recommendations for your system.

Packaging / Weight

Drum 525 lb 250 kg
IBCs/Totes 2,204 lb 1,000 kg

Physical Properties

Appearance Colorless liquid
Odor Slight
Solids content 40% w/w
Specific gravity 1.22 at 20/20°C
pH of undiluted 4.0

product

Viscosity 90mm²/s at 25°C Boiling point range 101-103°C (213-2

Boiling point range 101-103°C (213-217°F)

Freezing point range -1 to -3°C (30-27°F)

Freezing point range Theoretical

phosphorus Content

(as P)

Solubility in:

-Water -Ethylene glycol

-Methanol

-46% caustic soda pH limitations

Miscible Miscible

0.7% (w/w)

Precipitate is formed

Miscible

Does not form insoluble sodium or potassium salts. It is hydrolytically stable and can be incorporated into concentrated

formulations regardless

of the final pH.

Further details are available in the safety data sheet

^{*}Consult your sales representative for availability.



info@lenntech.com Tel. +31-152-610-900 www.lenntech.com Fax. +31-152-616-289

Patents:

BWA Water Additives (BWA) owns or is the licensee of patents and patent applications, which may cover the products and/or uses described in this brochure.

The following are registered trademarks of BWA Belclene, Belcor, Belgard, Belite, Bellacide, Bellasol, Belsperse, BromiCide, Flocon, Geogard and Liquibrom Drop and Swirl logo. ® Registered US Patent and Trademark Office. © 2016 BWA all rights reserved.

The information contained in this product sheet is based on data available to BWA Water Additives at the time of publication. While BWA has made every effort to ensure this information is correct, no responsibility can be accepted by BWA for any loss or liability occasioned by any person acting or refraining from acting as a result of the contents of this publication. BWA cannot guarantee that the results described in this information will be achieved by others if BWA has not participated in the testing process. BWA therefore makes no warranty of merchantability or fitness for a particular purpose or any express or implied warranty in respect of this information. This information is intended for use by technically trained personnel at their discretion and risk and is not a substitute for specific professional or technical advice. BWA's liability shall be limited by its standard limitations of liability contained within its standard terms and conditions of sale if BWA makes any sales to you.

© 2016 all rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means or stored in any retrieval system without the prior written permission of BWA Water Additives UK Limited. BWA Water Additives UK Limited is a private limited company registered in England and Wales at 2 Brightgate Way, Manchester M32 0TB, Registered No. 5657343.