

Clack®

LENNTECH
WATER TREATMENT SOLUTIONS

WS1EE TWIN ALTERNATING CONTROL VALVE

WATER SPECIALIST CONTROL VALVE



Certified to NSF/ANSI 44, 61 and 372.

- Service flow 28 gpm, backwash flow 15 gpm with meter and bypass installed
- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, days until next regeneration, volume remaining, current flow rate and total volume used (Totalizer), and Tank in Service Indication
- Four methods to initiate regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Optional double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Adjustable cycle times with 6-cycle control delivers controlled backwash, downflow brining/slow rinse, second backwash, fast rinse, refill and downflow service
- Coin Cell Lithium battery back-up with a 8 hour carry over
- Backwash and brining ability to 21" diameter tanks
- Downflow or upflow brining regeneration
- 12-volt output AC Adapter provides safe and easy installation
- Treated/Soft water post fill and regeneration cycles
- Patented one piece expanding seal spacer stack assembly U.S. Patent 6,402,944
- Patented linearly reciprocating piston operation U.S. Patent 6,444,127
- Reliable and proven DC drives

Water Specialist 1" EE Twin Alternating Specifications

Inlet/Outlet Fittings..... ¾" to 1.5" NPS
 Cycles up to 6
 Valve Material Noryl (1) or equivalent
 Regeneration downflow

FLOW RATES

Service @15 psi drop (includes bypass and meter) 28 gpm
 Backwash @ 25 psi drop (includes bypass) 15 gpm
 Cv Service 7.28
 Cv Backwash 2.96

OPERATING PRESSURES

Minimum/Maximum 20 psi – 125 psi

OPERATING TEMPERATURES

Minimum/Maximum 40° – 110° F

METER

Accuracy ± 5%
 Flow Rate Range..... 0.25 – 30 gpm
 Gallon Range..... 20 – 1,500,000 gallons
 Totalizer 1000 - 9,999,000 gallons

DIMENSIONS & WEIGHT

Distributor Pilot..... 1.050" OD Pipe (¾" NPS)
 Drain Line ¾" or 1" Male NPT
 Brine Line ⅜" or ½" OD Poly Tube Compression
 Mounting Base..... 2 ½" - 8 NPSM
 Height From Top Of Tank..... 7 ⅜"
 Weight 16 lbs.

ELECTRICAL SPECIFICATIONS

AC Adapter

	<u>U.S.</u>	<u>International</u>
Supply Voltage	120V AC.....	230V AC
Supply Frequency	60 Hz	50 Hz
Output Voltage	12V AC.....	12V AC
Output Current	500 mA.....	500 mA

TANK APPLICATIONS

Water Softener 6" – 21" diameter
 Water Filter (2)..... 6" – 16" diameter

CYCLES OF OPERATION (Softener / Filter Downflow)

	<u>Softener</u>	<u>Filter</u>
Cycle	Range of time in minutes	
1. Backwash 1 st	1-120.....	Backwash 1-120
2. Regenerate Draw/Slow Rinse	1-180	
3. Backwash 2 nd	1-120	
4. Fast Rinse	1-120.....	Rinse 1-120
5. Regenerant Refill	0.1-99.0 or off	
6. Service (downflow)		

Options: Backwash Filter, Bypass, Weather Cover

Compatible with the following typical concentration of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. Noryl is a trademark of Sabic Innovative Plastics IP B.V. Company
2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area

LENNTECH

info@lennotech.com Tel. +31-152-610-900
 www.lennotech.com Fax. +31-152-616-289