


Technical data Corode filter unit

CF20..M

20800l/h – Filter housing PP

Corode unit with magnetic drive pump CPMD-20.

Q max :20.8m³/h
 Q min :3m³/h
 Pump head :PP
 Motor :1.5kW, 400V, 5.42/3.15Amp, 3Ph, 50Hz, IP55
Other voltage options and 60Hz available on request.



Filter housing in PP maximum temp 80°C
 Outside metal SS316
 Height filter housing: 20", 30"

Standard units include:

Thermal overload switch
 Air release/ drain valve
 Pressure gauge

Filter media:

Cartridge, paper

Optional:

Dry run protector
 Hand priming pump
 Transport wheels
 Precoat tank PP 20"xØ310 (36 liter)

	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m ²
CF20CM PP	60	50	120	Ø50mm	Ø50mm	Cartridge 15x20"	9.90
CF20PM PP	60	50	120	Ø50mm	Ø50mm	Paper 66xØ295	4.30
CF20C30M PP	60	50	145	Ø50mm	Ø50mm	Cartridge 15x30"	14.85
CF20P30M PP	60	50	145	Ø50mm	Ø50mm	Paper 95xØ295	6.45