

## Technical data Corode filter unit



# FIL04..M

## 3500l/h – Filter housing PP

Corode unit with magnetic drive pump **MAG-04**.

Q max :3.5m<sup>3</sup>/h  
 Q min :0.6m<sup>3</sup>/h  
 Pump head :PP or PVDF  
 Motor :0.12kW, 400V, 0.66/0.38Amp, 3Ph, 50Hz, IP55  
 :0.12kW, 230V, 1.1Amp, 1Ph, 50Hz, IP55

Filter housing in PP maximum temp 80°C  
 Filter housing in PP maximum temp 100°C  
 Outside metal SS316  
 Height filter housing: 10", 20"

### Standard units include:

Thermal overload switch  
 Air release/ drain valve  
 Pressure gauge

### Filter media:

Cartridge, paper

### Optional:

Dry run protector  
 Hand priming pump  
 Transport wheels  
 Precoat tank PP 10"xØ225 (10 liter)  
 20"xØ225 (20 liter)

	L in cm	W in cm	H in cm	Connection suction pump	Connection outlet filter unit	Filter media	Filter area in m <sup>2</sup>
<b>FIL04C3M PP</b>	45	35	85	Ø25mm	Ø25mm	Cartridge 3x10"	0.99
<b>FIL04P3M PP</b>	41	35	85	Ø25mm	Ø25mm	Paper 36xØ136	0.45
<b>FIL04C32M PP</b>	45	35	110	Ø25mm	Ø25mm	Cartridge 3x20"	1.98
<b>FIL04P32M PP</b>	45	35	110	Ø25mm	Ø25mm	Paper 75xØ136	0.90
<b>FIL04CM PP</b>	45	35	85	Ø25mm	Ø25mm	Cartridge 7x10"	2.31
<b>FIL04PM PP</b>	45	35	85	Ø25mm	Ø25mm	Paper 41xØ215	1.25
<b>FIL04C20M PP</b>	45	35	110	Ø25mm	Ø25mm	Cartridge 7x20"	4.62
<b>FIL04P20M PP</b>	45	35	110	Ø25mm	Ø25mm	Paper 77xØ215	2.30
<b>FIL04C3M PVDF</b>	45	35	85	Ø25mm	Ø25mm	Cartridge 3x10"	0.99
<b>FIL04C32M PVDF</b>	45	35	110	Ø25mm	Ø25mm	Cartridge 3x20"	1.98
<b>FIL04C5M PVDF</b>	45	35	85	Ø25mm	Ø25mm	Cartridge 5x10"	1.65



info@lenntech.com Tel. +31-152-610-900  
 www.lenntech.com Fax. +31-152-616-289