

**DOWEX IF-59**

A Floating Inert Resin Specially Designed for use in Upflow Service Ion Exchange Packed Bed Counter-Current Regeneration Systems

Product	Type	Matrix	Functional group
DOWEX™ IF-59	Inert resin	Polypropylene	None

**Typical Physical and Chemical Properties**

Bead size distribution <sup>†</sup>			
Range 1,000 - 1,700 µm (18 mesh - 12 mesh)	%		95
< 1,000 µm, max. (18 mesh)	%		1
Particle density	g/mL		0.97
Shipping weight	g/L		560
	lbs/ft <sup>3</sup>		35

**Recommended Operating Conditions**

- Maximum operating temperature 100°C (212°F)
- pH range 0 - 14
- Bed depth, min. 150 mm (0.5 ft)
- Flow rates:  
Service 5 - 60 m/h (2 - 24 gpm/ft<sup>2</sup>)

**Typical Properties and Applications**

DOWEX IF-59 resin has a density less than water which insures it stays above the ion exchange resin bed. It protects the collector system against blockage and prevents resin fragments from being flushed from the bed during the service cycle.

**Packaging**

25 liter bags

<sup>†</sup> For additional particle size information, please refer to Particle Size Distribution Cross Reference Chart (Form No. 177-01775)

Warning: Oxidizing agents such as nitric acid attack organic ion exchange resins under certain conditions. This could lead to anything from slight resin degradation to a violent exothermic reaction (explosion). Before using strong oxidizing agents, consult sources knowledgeable in handling such materials.

Notice: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. **NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

