

# 91. Recommended spare parts: AMD, AMG, AFG, SRP


## 50/60 Hz

### Customer Information

Project title:	Customer name:
Reference number:	Customer number:
Customer contact:	Customer phone number: ( )
	Fax number: ( )

### Pump information

### Quotation made by

Type	Prod. No.	
P.c.	∅ mm	No.
▽	T °C	IP
Model	Pol	Hz
P./P <sub>2</sub>	kW	I <sub>N</sub>
Cos.φ		A <sub>Start</sub> A <sub>N</sub> /min
Ex		Weight kg
 CH-6105 Schachen		

Company name:

Prepared by:

Phone number: ( )

Fax number: ( )

Date:

Quote number:

### Recommended spare parts

	Recommended service parts				Product number
	AMD.XX.45		AMG, AFG, SRP		
Kit - Spare - Bulk	2 years units per pump	5 years units per pump	2 years units per pump	5 years units per pump	
Kit, Shaft seal, outer	1	3			
Kit, Shaft seal, inner		1			
Kit, Bearing		1			
Kit, Sealing		1		1	
Kit, Radial sealing			2	4	
Kit, Shaft seal				1	
Kit, Bearing motor				1	
Oil*	1	3		1	

\* See service instruction for amount and type.

Above recommendations are based on:

Agitators running in normal operation should be checked every 3000 operating hours or at least once a year.  
If the stirred liquid is very muddy or sandy, check the pump at shorter intervals.