



- Energy saving thanks to higher hydraulic performances
- Dry running protection
- Self-priming pump
- Stainless steel pump body
- Pump longer life-time
- Protection against motor overload and
- Water temperature overheating

Model: **EVO-MULTIMAX
550 LOGIC SAFE**
 Part number: **N4501310**
 Barcode: **7630014570010**


Self priming surface pump with multistage hydraulic system and stainless steel pump body.
 EVO-MULTIMAX 550 LOGIC SAFE is equipped with LOGIC SAFE, an integrated electronic device for protection against dry running, motor overload and water temperature overheating.


LENNTECH
 WATER TREATMENT SOLUTIONS

info@lennotech.com Tel. +31-152-610-900
 www.lennotech.com Fax. +31-152-616-289

APPLICATIONS

Irrigation of lawns and flowerbeds
 Washing of terraces or outdoors floors
 Basins or expansion tanks filling/drainage

ABSORBED POWER	1350 W	POWER CABLE	1.5 m
VOLTAGE	230 V	SUCTION/DELIVERY PORT.	33.25 mm (1" F)
FLOW RATE	7800 l/h	MAX. ADVISED SUCTION HEAD	8 m
MAX. HEAD	62 m	WEIGHT	10.6 kg
RATED CURRENT	6.2 A	PACKAGING DIMENSIONS	43.3 x 23.6 x 25.3 cm
N° IMPELLERS	5	PCS PER PALLET	28
PROTECTION CLASS	IPX5	ACCESSORIES	-
PUMP BODY	Stainless Steel		x 5

2+1 2 YEARS GUARANTEE +
 1 YEAR WARRANTY
 2 ANS GARANTIE LÉGALE +
 1 AN GARANTIE COMMERCIALE

