



- Stainless steel pump body and motor shaft
- Double mechanical seal for great reliability, reduction of maintenance operations and continuous duty.
- Integrated check valve
- 20 m safety rope

Model: **SUB 8 S PLUS  
AUTO**  
Part number: **N3200200-P**  
Barcode: **7630014535286**

Submersible pump with asynchronous single phase motor, stainless steel pump body and motor shaft. SUB 8S Plus AUTO has a mechanical seal in graphite and reinforcement in ceramic, built-in condenser and integrated check valve. Dry running protection thanks to PRESSUREMATE device.




**LENNTECH**  
WATER TREATMENT SOLUTIONS

info@lennotech.com Tel. +31-152-610-900  
www.lennotech.com Fax +31-152-616-289

#### APPLICATIONS

Irrigation of lawns and flowerbeds  
Washing of terraces or outdoors floors  
Basins or expansion tanks filling/drainage

<b>ABSORBED POWER</b>	1100 W	<b>POWER CABLE</b>	22 m H07 RN-8F
<b>VOLTAGE</b>	230 V	<b>SUCTION/DELIVERY PORT.</b>	41.90 mm (1 1/4")
<b>FLOW RATE</b>	6000 l/h	<b>MAX. WATER TEMPERATURE</b>	40°C
<b>PRESSURE/MAX. HEAD</b>	57 m	<b>WEIGHT</b>	13.2 kg
<b>RATED CURRENT</b>	5 A	<b>PACKAGING DIMENSIONS</b>	75 x 33 x 12 cm
<b>N° IMPELLERS</b>	8	<b>PCS PER PALLET</b>	20
<b>MIN. OPERATING SPACE</b>	100 mm	<b>ACCESSORIES</b>	-
<b>MAX. IMMERSION DEPTH</b>	19 m		x 5