

# Retention Vessels

## Product Features

- The vessel of choice for chemical treatment
- Provides optimal contact time
- FDA and/or NSF-approved materials
- Seamless inner shell of molded polyethylene for impact and corrosion resistance
- Miles of epoxy covered fiberglass filament for superior strength and light weight
- Inlet/outlet PVC pipe connections offer application flexibility
- Adaptable for both new and replacement installation
- Additional drain port
- Factory-backed five-year warranty

## Materials of Construction

- Polyethylene inner shell

## Operating Parameters

- Maximum operating pressure: 75 psi
- Maximum operating temperature: 120°F



**LENNTECH**

info@lennotech.com Tel. +31-152-610-900  
www.lennotech.com Fax. +31-152-616-289

# Specifications

Part No.	Model	Size (Inches)	System Connections (PVC) Top	Height Bottom	Capacity Inches / mm	Gallons / Liters	Cubic Feet Nominal
31534	CT-30	16 x 40	1-1/4" female NPT	1-1/4" male	44.0 / 1112.0	30.0 / 113.5	4.0 NPT
31533	CT-40SQ	21 x 32	1-1/4" female NPT	1-1/4" male	35.0 / 889.0	40.0 / 151.2	5.3 NPT
31608	CT-40	16 x 53	1-1/4" female NPT	1-1/4" male	56.0 / 1422.0	40.0 / 151.2	5.3 NPT
30957	CT-80	24 x 50	1-1/4" female NPT	1-1/4" male	67.0 / 1702.0	80.0 / 302.4	10.7 NPT
31057	CT-120	24 x 70	1-1/4" female NPT	1-1/4" male	73.0 / 1854.2	120.0 / 454.0	16.0 NPT

