

PRODUCT DATA SHEET

Purolite® IP4

Polypropylene, Inert Polymer,
Upflow Service Packed Beds
(Puropack), Cylinder shape

LENNTECH
WATER TREATMENT SOLUTIONS

PRINCIPAL APPLICATIONS

- Strainer guard for Puropack systems
- Strainer guard for upflow service packed bed systems

ADVANTAGES

- Protects upper nozzle plates from blockage
- Improves the distribution of regenerants during downflow regeneration
- Floats in water

SYSTEMS

- Upflow service packed bed systems
- Puropack packed bed systems

REGULATORY APPROVALS

- IFANCA Halal Certified
- Kosher Certified

TYPICAL PACKAGING

- 1 CF Box
- 5 ft³ Drum (Fiber)
- 42 ft³ Supersack

TYPICAL PHYSICAL & CHEMICAL CHARACTERISTICS:

Polymer Structure	Polypropylene
Appearance	Cylinders
Diameter	1.1 - 1.5 mm
Length	0.8 - 1.6 mm
Specific Gravity	0.8 - 0.9
Shipping Weight (approx.)	520 - 550 g/L (32.5 - 34.4 lb/ft ³)
Temperature Limit	100 °C (212.0 °F)



LENNTECH

info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289