

## BetzDearborn\* CP1159

- Increases Efficiency of Sludge Dewatering Operations
- Improves Effluent Quality
- Cost Effective

### description and use

BetzDearborn\* CP1159 is a medium molecular weight, low charge density, cationic polymer. This polymer performs excellently as a sludge conditioning agent or flocculant. It is designed to function in a total SUEZ treatment programme improving surface or wastewater quality.

### typical applications

BetzDearborn CP1159 is very effective in sludge dewatering operations. Benefits such as higher solids capture, drier cake and cleaner effluent are seen in paper industry and other types of industrial sludges.

Floc carryover is reduced in both waste and influent clarification/thickening systems where BetzDearborn CP1159 is applied. A large, fast settling agglomerate forms to produce a clean effluent. Performance in secondary clarification/ thickening systems demonstrates the excellent flocculating characteristics of this polymer.

The application of BetzDearborn CP1159 to coke plant pipeline charging systems improves solids removal from charging liquor and increases the capacity of settling equipment.

When used as part of a SUEZ Rec-Oil\* treatment programme, BetzDearborn CP1159 improves oil, water

## Water Technologies & Solutions fact sheet

and suspended solids separation in refinery, automotive and steel mill oily wastewater treatment.

Any operation requiring a fast settling agglomerate, or a well flocculated sludge will benefit from the use of BetzDearborn CP1159.

### treatment and feeding requirements

BetzDearborn CP1159 may be prepared in batch fashion by slowly adding the powder to the vortex of an agitated tank, using a dry feeder or an eductor. Do not add water to dry polymer. Maximum practical solution concentration is 0.5% by weight. Air or low speed (400 rpm) mechanical agitation should continue until complete dissolution is accomplished in one to two hours.

Avoid degrading the polymer with water temperature in excess of 37°C and high shear agitation once the BetzDearborn CP1159 has been made down. It is recommended that dilute solutions be used within 24 hours for maximum activity.

Further dilution of the stock solution to approximately 0.05% by weight, or 10 to 1, enhances polymer performance in most applications. For dewatering applications dilution to approximately 0.25% often gives optimum performance.

Proper treatment levels for BetzDearborn CP1159 depend on many factors such as severity of the problem and conditions particular to a given installation. The product is to be used in accordance

with control procedures SUEZ establishes for a specific application.

### **packaging information**

BetzDearborn CP1159 is available in a wide variety of customised containers and delivery methods. For more information please contact your SUEZ representative.

### **safety precautions**

A Material Safety Data Sheet containing detailed information about this product is available on request.

**LENNTECH**

info@lenntech.com Tel. +31-152-610-900

www.lenntech.com Fax. +31-152-616-289