

Memtrex* MP-S

pleated filters with polyethersulfone membrane

Water Technologies & Solutions fact sheet



Figure 1: Memtrex MP-S Pleated Filters

description and use

Our commitment to validation is based upon the FDA Guidelines that we establish documented evidence of assurance that a specific process will consistently produce a product meeting its predetermined specification and quality attributes. Memtrex* MP-S filters (Figure 1) are designed for final sterile filtration of biological and pharmaceutical products. The double-layer PES membrane provides low protein-binding, high throughput and broad chemical compatibility for your critical filtration processes.

A detailed Validation Guide is available from SUEZ to document our rigorous testing for your records and reviews. The guide includes all the data necessary to assist the user with compliance to regulatory requirements.

The Memtrex MP-S filter is just one example of our strong commitment to the pharmaceutical industry. Our complete portfolio includes filters for every stage of processing, and we offer custom solutions for your unique applications. SUEZ is your complete source for filters, crossflow membranes, housings, and other filtration equipment.

typical applications

Memtrex MP-S filters are specifically designed for sterile filtration of pharmaceutical and biological products. Typical applications include:

- Final Filtration of Drugs and Biologicals
- Final Filtration of Water for Injection
- Final Filtration of Pure Water for Dialysis
- LVPs, SVPs
- Diagnostics
- Tissue Culture Media
- Vaccines

general properties

Memtrex MP-S filters are available with an absolute pore size micron rating of 0.2 µm. Tables 1, 2, 3, and 4 show further details on materials of construction, dimensions, operational limits, and flow performance.

Table 1: Materials of Construction

Media	2 layers of Hydrophilic Polyethersulfone
Support Layers	Polypropylene Microfiber
Core and Cage	Polypropylene
Endcaps and Adapters	Polypropylene with Stainless Steel Insert

Table 2: Dimensions

Nominal O.D	Nominal I.D.	Effective Filtration Area
2.75" (70mm)	1.25" (31mm)	6.5 ft ² (0.60 m ²)

Integrity Testing

Air diffusion per 10" module after saturation with clean water. <12 cc/min at 40 psig (2.76 bar)

Table 3: Operational Limits


Maximum Forward Differential Pressure	60 psi (4.14 bar)
Maximum Reverse Differential Pressure	30 psi (2.07 bar)
Maximum Operating Temperature	180°F (82°C) at 10 psid (0.69 bar) in water

additional information

- Memtrex MP-S filters may be autoclaved or in situ steam sterilized (up to 257°F [125°C], 30-minute cycles) for a maximum accumulated exposure of 10 hours. Alternately, the filters may be sanitized with compatible chemical agents.
- SUEZ certifies that the material contained in its Memtrex MP-S pleated filters meet U.S. FDA requirements for food contact under the applicable regulations in 21 CFR. For further information, contact SUEZ technical services. Memtrex MP-S filters meet the test criteria for USP class VI-121°C Plastics.
- Aqueous extracts from Memtrex MP-S filters contain less than 0.25 EU/ml. The filters typically exhibit low levels of non-volatile residues.
- SUEZ filter cartridges are designed and manufactured for resistance to a wide range of chemical solutions. Conditions will vary with each application and users should carefully verify chemical compatibility. Please contact your SUEZ distributor for more information.
- Table 5 provides additional ordering information.

Table 5: Ordering Information

Table 4: Flow Performance in Clean Water¹



¹ Data based on 10" length filter



LENNTECH
 info@lenntech.com Tel. +31-152-610-900
 www.lenntech.com Fax. +31-152-616-289

Type	Absolute Micron Rating	Nominal Cartridge Length	End #1 Adapter	End #2 Adapter	Elastomer Material	Grade
MMP-S	92 = 0.2 µm	1 = 10 Inch (25 cm) 2 = 20 Inch (51 cm) 3 = 30 Inch (76 cm) 4 = 40 Inch (102 cm)	Q = 222 O-Ring Stainless Steel Support Ring Z = 226 O-Ring Stainless Steel Support Ring	A = Open End Gasket B = 120 O-Ring C = 213 O-Ring G = Closed End Cap H = Fin Adapter	S = Silicone	S = Sterilizing