

Water Technologies & Solutions fact sheet

Hypersperse* MDC712

antiscalant / antifoulant

- Excellent results in seawater applications
- Highly effective over a wide range of waters – for calcium-based and sulfate-based scales, notably, barium sulfate
- Compatible with all of the leading RO membranes
- Maintains cleaner membrane surfaces by inhibiting scale and dispersing particulate foulants
- Effective over a wide pH range
- May be fed neat or diluted
- Compatible with feedwaters that contain aluminum and iron oxides

description and use

Hypersperse MDC712 is a highly effective liquid antiscalant/antifoulant developed to control scale precipitates and reduce particulate fouling within membrane separation systems. This highly effective liquid antiscalant/antifoulant can be used with all SoliSep* coagulants. It is imperative that the coagulants used are compatible with the antiscalant/antifoulant being injected as incompatible chemicals may cause membrane fouling. This antiscalant was designed to work on seawater applications. It protects the membrane from scale formation using very low dosages.

application

For maximum effectiveness, Hypersperse MDC712 should be added prior to the static mixer or cartridge filter housing.

dosing

Typical dosage range is between 0.4 and 0.6 mg/L.

Please contact your local SUEZ representative to define the optimal feed point and dosage rate.

Maximum Dilutions

Maximum dilution is temperature related as shown:

Temperature	Maximum Dilution %
<30°C	10
30 – 35°C	25
>35°C	50

packaging information

Hypersperse MDC712 is a liquid material, available in a wide variety of customized containers and delivery methods. Contact your SUEZ sales representative for details.

storage and handling

Keep from freezing.

safety precautions

A Material Safety Data Sheet (MSDS) containing detailed information about this product is available on request.



info@lennotech.com Tel. +31-152-610-900
www.lennotech.com Fax. +31-152-616-289